

Eaton C25DND325T

Catalog number: C25DND325T

Eaton definite purpose contactor, Quick, 25A, 24 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 25A, Contactor, Three-pole, 35A, Screw/pressure plate and quick connect terminals (side-by-side), Non-reversing

General specifications



Product Name	Catalog Number
Eaton definite purpose contactor	C25DND325T
UPC	Product Length/Depth
782116300563	3.35 in
Product Height	Product Width
3.75 in	2.4 in
Product Weight	Warranty
1.19 lb	1 year
Compliances	Certifications
RoHS Compliant	CSA Certified UL Recognized

defaultTaxonomyAttributeLabel

Frame size

15-50 A, two-pole and three-pole

Type

Non-reversing

Inductive full load

25 A

Model

Contactors

Connection

Quick

Enclosure

Open with metal mounting plate

Terminals

Screw/pressure plate and quick connect terminals (side-by-side)

Amperage Rating

25A

Resistive load

35 A

Coil

24 Vac, 50/60 Hz

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25DND3 3D Inventor](#)

[C25DND3 3D Model Xchange](#)

[C25DND3 2D PDF](#)

[C25DND3 AutoCAD 2D Footprint \(mm\)](#)

[C25DND3 AutoCAD 2D Footprint](#)

[C25DND3 2D Drawing Xchange](#)

Specifications and datasheets

[Eaton Specification Sheet - C25DND325T](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)