

Eaton P48G11S05CUB

Catalog number: P48G11S05CUB

Eaton Mini-Power Center, Single-phase, PV: 480V, Taps: 2 at -5% FCBN, SV: 120/240V, 115°C, 5 kVA, Cu windings , Frame: 307, Indoor-Outdoor.



General specifications

Product Name

Eaton Mini-Power center

Catalog Number

P48G11S05CUB

UPC

786680034640

Product Length/Depth

9.66 in

Product Height

36.14 in

Product Width

12.56 in

Product Weight

151 lb

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances

NEMA Compliant

Certifications

UL Listed CSA Certified IEEE Certified ANSI

Catalog Notes

All copper construction (coil and interior) and accepts bolt-on branch breakers from the BAB family

Physical Attributes

Coil material

Copper

Enclosure

NEMA 3R

Frame

307

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

110A5K

Performance Ratings

Phase

Single-phase

Primary voltage

480 V

Secondary Voltage

120/240 V

Temperature rise

115 °C rise

Volt ampere rating

5 kVA

Miscellaneous

Weathershield

Indoor-Outdoor

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P48G11S05CUB](#)