

Eaton SL7-AP24

Catalog number: SL7-AP24

Acoustic Module, SL7, 70 mm, Continuous or pulsed tone, adjustable, 92A max., 24 Vac/Vdc, Black, 100 dB, 2800 Hz, Internal DIP switch, internal potentiometer, (1), UL type 4, 4X, 13 , IP66

General specifications



Product Name	Catalog Number
Eaton SL7 stacklight acoustic module	SL7-AP24
EAN	Product Length/Depth
4015081678105	3.25 in
Product Height	Product Width
3 in	3 in
Product Weight	Warranty
.25 lb	2 year
Compliances	Certifications
CE Marked	CSA Certified cULus Listed UL Listed UL 508 CSA Std. C22.2 No. 14-10 UL Listed file E29184 CSA Std. C22.2 No. 94-91 CSA Class No. NKCR7 IEC Rated

defaultTaxonomyAttributeLabel

Accessories

Internal DIP switch, internal potentiometer

Series

SL7

Type

70 mm

Frequency rating

2800 Hz

Decibel

100 dB

Color

Black

Model

Adjustable

Pulsed tone

Continuous

Environmental rating

IP66

Quantity

1

Enclosure

UL type 4, 4X, 13

Voltage rating

24 Vac/Vdc

Rated operational current

92 A maximum

Resources

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - SL7-AP24](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)