

Eaton PSG480R24RM

Catalog number: PSG480R24RM

Eaton PSG Power Supply, Aluminum, 47-63 Hz, Redundancy module, Finger-safe terminals, 24 Vdc output, 960W output power, -40°C-80°C operating temp



General specifications

Product Name	Catalog Number
Eaton PSG general purpose power supply	PSG480R24RM
	UPC
	786685878430
Product Length/Depth	Product Height
6.4 in	2.9 in
Product Width	Product Weight
6.6 in	1.2 lb
Warranty	Compliances
3 year	CE Marked RoHS Compliant
Certifications	
UL 508 CSA Std. C22.2 IEC Rated EN Listed	

defaultTaxonomyAttributeLabel

Enclosure color

Aluminum

Type

Redundancy module

Operating temperature - min

-40 °C

Operating temperature - max

80 °C

Frequency rating

47-63 Hz

Output

960 W

Terminals

Finger-safe

Output voltage

24 V

Resources

Brochures

[Eaton's PSG Series Power Supplies](#)

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Drawings

[PSG480R24RM AutoCAD 2D Footprint \(mm\)](#)

[PSG480R24RM AutoCAD 2D Footprint](#)

[PSG480R24RM 3D Model Xchange](#)

[PSG480R24RM 2D Drawing Xchange](#)

[PSG480R24RM 2D PDF](#)

[PSG480R24RM 3D Inventor](#)

Installation instructions

[Installation Instructions for PSG480F Power Supply](#)

Multimedia

[How to size and select a Power Supply](#)

Specifications and datasheets

[Eaton Specification Sheet - PSG480R24RM](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)