

Eaton XTCEXFAC04

Catalog number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC04
UPC	Product Length/Depth
782116354559	1.5 in
Product Height	Product Width
1.3 in	1.5 in
Product Weight	Compliances
.12 lb	CCC Marked CE Marked ATEX Compliant
Certifications	Catalog Notes
IEC 60947 EN 60947 UL Listed CSA Certified	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

defaultTaxonomyAttributeLabel

Contact configuration

4 NC

Special features

Used with XTRE control relays

Type

Contactory Accessory - Auxiliary Contact

Used with

XTRE control relays

Quantity

5

Terminals

Screw

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Conventional thermal current

16A

Number Of Poles

Four-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)

[Global Data Sheet - XTCEXFAC04](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)