

Eaton XTMR9A21A

Catalog number: XTMR9A21A

Eaton XT IEC mini contactor, 8.80A, 110 Vac 50 Hz, 120 Vac 60 Hz, 2NO-2NO, 45 mm mini, 50-60 Hz, 0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR

General specifications



Product Name

Eaton XT IEC mini contactor

Catalog Number

XTMR9A21A

UPC

782116884339

Product Length/Depth

5.25 in

Product Height

5 in

Product Width

5.75 in

Product Weight

1.2 lb

Warranty

1 year

Compliances

CE Marked RoHS Compliant

Certifications

CSA Certified UL Listed IEC 60947 EN 60947

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Contact configuration

2 NO, 2 NO

HP rating - max

0.5, 1, 1.5/ 2, 3, 5, 5 hp (1/3PH @ 115,200,230/200,230,460,575 V)

Operation

Non-reversing

Amperage Rating

8.80A

Number Of Poles

Three-pole

Coil

110-120 Vac, 50/60 Hz

Frame size

45 mm - mini

Coil voltage

110-120 Vac, 50/60 Hz

Series

XT IEC

Type

Full voltage non-reversing mini contactor

Continuous ampere rating

8.80 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTMR AutoCAD 2D Footprint](#)

[XTMR AutoCAD 2D Footprint \(mm\)](#)

[XTMR 3D Inventor](#)

[XTMR 2D PDF](#)

[XTMR 3D Model Xchange](#)

[XTMR 2D Drawing Xchange](#)

Multimedia

[S1. E4. Ask the Experts - NEMA, IEC and DP contactors](#)

[Contactors Explained](#)

Specifications and datasheets

[Eaton Specification Sheet - XTMR9A21A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)