

Eaton XTCR080F11A

Catalog number: XTCR080F11A

Eaton XT IEC contactor, 80A, Top-mounted, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO-1NC, 80A, Frame F, 90 mm, 50-60 Hz, 7.5, 15/ 25, 30, 60, 75 hp (1/3PH @115, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVR



General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCR080F11A
UPC	Product Length/Depth
782116356126	9.5 in
Product Height	Product Width
6 in	6.5 in
Product Weight	Compliances
4.7 lb	CE Marked RoHS Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Contact configuration

1 NO, 1 NC

Coil voltage

110-120 Vac, 50/60 Hz

Series

XT IEC

Type

Full voltage reversing contactor

HP rating - max

7.5, 15/ 25, 30, 60, 75 hp (1/3PH @115,230/200,230,460,575 V)

Continuous ampere rating

80 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Operation

Reversing

Amperage Rating

80A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCR_F 3D Inventor](#)

[XTCR_F 3D Model Xchange](#)

[XTCR_F AutoCAD 2D Footprint \(mm\)](#)

[XTCR_F 2D Drawing Xchange](#)

[XTCR_F AutoCAD 2D Footprint](#)

[XTCR_F 2D PDF](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCR080F11A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)