

Eaton XTCF032C10A

Catalog number: XTCF032C10A

Eaton XT IEC contactor, 32A, 110 Vac 50 Hz, 120 Vac 60 Hz, 1NO, 32A, Frame C, 45 mm, 50-60 Hz, 7.5, 7.5, 10, 15 hp (3PH @200, 230, 460, 575 V), Four-pole, Non-reversing, Screw terminals, FVNR

General specifications



Product Name

Eaton XT IEC contactor

Catalog Number

XTCF032C10A

EAN

4015081093625

Product Length/Depth

5.43307087 in

Product Height

3.34645669 in

Product Width

2.28346457 in

Product Weight

.48501698 lb

Compliances

CE Marked RoHS Compliant

Certifications

UL Listed CSA Certified IEC 60947 EN 60947

Catalog Notes

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Contact configuration

1 NO

Coil voltage

110-120 Vac, 50/60 Hz

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

7.5, 7.5, 10, 15 hp (3PH @200,230,460,575 V)

Continuous ampere rating

32 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

32A

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCF_C 2D PDF](#)

[XTCF_C AutoCAD 2D Footprint](#)

[XTCF_C 2D Drawing Xchange](#)

[XTCF_C 3D Inventor](#)

[XTCF_C AutoCAD 2D Footprint \(mm\)](#)

[XTCF_C 3D Model Xchange](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCF032C10A](#)

[Global Data Sheet - XTCF032C10A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)