

Eaton XTOB220LC1

Catalog number: XTOB220LC1

Eaton XT IEC bimetallic overload relay, 160-220A overload range, 140 mm Frame size, 1NO-1NC contact configuration, used with 185-250A, 10A trip type



General specifications

Product Name	Catalog Number
Eaton XT IEC bimetallic overload relay	XTOB220LC1
EAN	Product Length/Depth
4015082100742	5.67 in
Product Height	Product Width
6.65 in	5.04 in
Product Weight	Compliances
3.5 lb	ATEX Compliant CE Marked RoHS Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Short-circuit Type 1 rating is 500A and short-circuit Type 2 rating is 400A for separate mounting. The main current parameters are defined by the main current wiring that is used.

defaultTaxonomyAttributeLabel

Frame size

140 mm

Contact configuration

1 NO, 1 NC

Overload range

160-220 A

Type

XT IEC Bimetallic Overload Relay

Used with

185-250A

Trip type

10 A

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_LC1 3D Inventor

XTOB_LC1 AutoCAD 2D Footprint

XTOB_LC1 AutoCAD 2D Footprint (mm)

XTOB_LC1 2D PDF

XTOB_LC1 2D Drawing Xchange

XTOB_LC1 3D Model Xchange

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Eaton Specification Sheet - XTOB220LC1

Global Data Sheet - XTOB220LC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia