

Eaton XTCE080F00T

Catalog number: XTCE080F00T

Eaton XT IEC contactor, 80A, 24 Vac, 50-60 Hz, ONO-ONC, 80A, Frame F, 90 mm, 50-60 Hz, 7.5, 15, 15/ 25, 30, 60, 75 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor



General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE080F00T
EAN	Product Length/Depth
4015082394066	6.2992126 in
Product Height	Product Width
6.69291339 in	4.37007874 in
Product Weight	Certifications
.5070632 lb	UL Listed CSA Certified

defaultTaxonomyAttributeLabel

Contact configuration

0 NO, 0 NC

Coil voltage

24 Vac, 50-60 Hz

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

7.5, 15, 15/ 25, 30, 60, 75 hp (1/3PH
@ 115,200,230/200,230,460,575 V)

Continuous ampere rating

80 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

80A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_F 3D Inventor](#)

[XTCE_F 3D Model Xchange](#)

[XTCE_F 2D Drawing Xchange](#)

[XTCE_F 2D PDF](#)

[XTCE_F AutoCAD 2D Footprint](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCE080F00T](#)

[Global Data Sheet - XTCE080F00T](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)