

# Eaton XTCE150G00TD

Catalog number: XTCE150G00TD

Eaton XT IEC contactor, 150A, 24-27 Vdc, 0NO-0NC, 150A, Frame G, 90 mm, 10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton XT IEC contactor	XTCE150G00TD
<b>EAN</b>	<b>Product Length/Depth</b>
4015082395919	6.2992126 in
<b>Product Height</b>	<b>Product Width</b>
6.69291339 in	4.37007874 in
<b>Product Weight</b>	<b>Compliances</b>
.61729433 lb	RoHS Compliant CE Marked
<b>Certifications</b>	<b>Catalog Notes</b>
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

## defaultTaxonomyAttributeLabel

### Contact configuration

0 NO, 0 NC

### Coil voltage

24-27 Vdc

### Series

XT IEC

### Type

Full voltage non-reversing contactor

### HP rating - max

10, 25, 30/ 40, 60, 125, 125 hp (1/3PH  
@115,200,230/200,230,460,575 V)

### Continuous ampere rating

150 A

### Terminals

Screw terminals

### Operation

Non-reversing

### Amperage Rating

150A

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTCE\\_G 3D Inventor](#)

[XTCE\\_G AutoCAD 2D Footprint](#)

[XTCE\\_G 2D Drawing Xchange](#)

[XTCE\\_G 2D PDF](#)

[XTCE\\_G 3D Model Xchange](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTCE150G00TD](#)

[Global Data Sheet - XTCE150G00TD](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)