

# Eaton XTRE10B22T

Catalog number: XTRE10B22T

XT IEC Control Relay, Screw terminals, 45 mm - standard Frame size, 2NO-2NC contact configuration, 24V 50/60 Hz coil, 10A conventional thermal rating, 6A at 220/230/240V; 4A at 380/400/415V rated operational voltage

## General specifications



### Product Name

Eaton XT IEC control relay

### Catalog Number

XTRE10B22T

### EAN

4015082764036

### Product Length/Depth

3 in

### Product Height

2 in

### Product Width

3 in

### Product Weight

.5 lb

### Certifications

UL Listed

## defaultTaxonomyAttributeLabel

### Frame size

45 mm - standard

### Contact configuration

2 NO, 2 NC

### Type

Control relay

### Terminals

Screw terminals

### Rated operational current

4 A at 380/400/415 V

6 A at 220/230/240 V

### Conventional thermal current

10A

### Coil

24 Vac, 50/60 Hz

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTRE 3D Inventor](#)

[XTRE 2D Drawing Xchange](#)

[XTRE AutoCAD 2D Footprint \(mm\)](#)

[XTRE 3D Model Xchange](#)

[XTRE AutoCAD 2D Footprint](#)

[XTRE 2D PDF](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTRE10B22T](#)

[Global Data Sheet - XTRE10B22T](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)