

Eaton XTCEXFAC13

Catalog number: XTCEXFAC13

Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 1NO-3NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC13
EAN	Product Length/Depth
4015082764258	2.5 in
Product Height	Product Width
7.1 in	4.5 in
Product Weight	Warranty
.01 lb	Not Applicable
Compliances	Certifications
CE Marked ATEX Compliant CCC Marked	IEC 60947 EN 60947 UL Listed CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

defaultTaxonomyAttributeLabel

Contact configuration

1 NO-3 NC

Type

Contactory Accessory - Auxiliary Contact

Used with

XTRE control relays

Quantity

5

Terminals

Screw

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Conventional thermal current

16A

Number Of Poles

Four-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC13](#)

[Global Data Sheet - XTCEXFAC13](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)