


Eaton XTCE032C10TD

Catalog number: XTCE032C10TD

Eaton XT IEC contactor, 32A, 24-27 Vdc, 1NO, 32A, Frame C, 45 mm, 3, 5, 5/ 10, 10, 20, 25 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, XT IEC series, Screw terminals, Full voltage non-reversing contactor



General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE032C10TD
EAN	Product Length/Depth
4015082772741	4 in
Product Height	Product Width
2 in	3.5 in
Product Weight	Compliances
1.25 lb	CE Marked RoHS Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Frame size

45 mm

Contact configuration

1 NO

Coil voltage

24-27 Vdc

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

3, 5, 5/ 10, 10, 20, 25 hp (1/3PH
@115,200,230/200,230,460,575 V)

Continuous ampere rating

32 A

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

32A

Number Of Poles

Three-pole

Coil

24 Vdc

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_C AutoCAD 2D Footprint](#)

[XTCE_C 2D Drawing Xchange](#)

[XTCE_C 3D Model Xchange](#)

[XTCE_C 2D PDF](#)

Specifications and datasheets

[Global Data Sheet - XTCE032C10TD](#)

[Eaton Specification Sheet - XTCE032C10TD](#)

Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)