

Eaton XTCE050D00B

Catalog number: XTCE050D00B

Eaton XT IEC contactor, 50A, 220 Vac 50 Hz, 240 Vac 60 Hz, ONO-ONC, 50A, Frame D, 55 mm, 50-60 Hz, 3, 7.5, 10/ 15, 20, 40, 50 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Screw terminals, FVNR



General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE050D00B
EAN	Product Length/Depth
4015082778293	2 in
Product Height	Product Width
3.5 in	4 in
Product Weight	Compliances
.5070632 lb	RoHS Compliant CE Marked
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

defaultTaxonomyAttributeLabel

Frame size

55 mm

Contact configuration

0 NO, 0 NC

Coil voltage

220-240 Vac, 50/60 Hz

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

3, 7.5, 10/ 15, 20, 40, 50 hp (1/3PH
@115,200,230/200,230,460,575 V)

Continuous ampere rating

50 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

50A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_D 2D Drawing Xchange](#)

[XTCE_D AutoCAD 2D Footprint](#)

[XTCE_D 2D PDF](#)

[XTCE_D 3D Model Xchange](#)

[XTCE_D 3D Inventor](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCE050D00B](#)

[Global Data Sheet - XTCE050D00B](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)