

Eaton XTOBP60CC1

Catalog number: XTOBP60CC1

Eaton XT IEC bimetallic overload relay, 0.4-0.6A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 18-32A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOBP60CC1

EAN

4015082784454

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

.5 lb

Compliances

ATEX Compliant RoHS Compliant CE Marked

Certifications

UL Listed CSA Certified IEC 60947 EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Overload range

0.4-0.6 A

Type

XT IEC Bimetallic Overload Relay

Used with

18-32A contactor

Trip type

10 A

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_CC1 AutoCAD 2D Footprint](#)

[XTOB_CC1 2D PDF](#)

[XTOB_CC1 3D Model Xchange](#)

[XTOB_CC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_CC1 3D Inventor](#)

[XTOB_CC1 2D Drawing Xchange](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Eaton Specification Sheet - XTOBP60CC1](#)

[Global Data Sheet - XTOBP60CC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)