

defaultTaxonomyAttributeLabel

Contact configuration

2 NO, 2 NO

Coil voltage

110-120 Vac, 50/60 Hz

Series

XT IEC

Type

Full voltage reversing contactor

HP rating - max

2, 5/ 7.5, 10, 15, 20 hp (1/3PH @115,230/200,230,460,575 V)

Continuous ampere rating

25 A

Frequency rating

50-60 Hz

Terminals

Screw terminals

Operation

Reversing

Amperage Rating

25A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCR_C 3D Inventor](#)

[XTCR_C AutoCAD 2D Footprint](#)

[XTCR_C 2D Drawing Xchange](#)

[XTCR_C AutoCAD 2D Footprint \(mm\)](#)

[XTCR_C 3D Model Xchange](#)

[XTCR_C 2D PDF](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCR025C21A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2022 Eaton
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)