

LED-TP-PF

Flexible Power Feed for Single Colour LED Tape Light
Cove, Under Cabinet & Millwork

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Mounting

This highly flexible blank connector is provided with a Flexi3M® high bond adhesive backing that provides secure mounting to smooth surfaces.


Linkable

With a DC 2.1 jack, this power feed connects single colour LED tape run to a 24V LED driver.



Description

The LED-TP-PF is a flexible power feed used to connect single colour LED tape to 24V LED driver with DC 2.1 jack. For indoor use only.



Notes: For additional options please consult your Liteline representative. 3M is a registered trademark of 3M corporation. Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide



LED-TP-PF
Flexible power feed for single colour LED tape light, 24V.

Compatible Fixtures



LED-TP1-12-xx
12" (305mm) Single colour LED tape light, 24V.



LED-TP2-12-xx
12" (305mm) Single colour high output LED tape light, 24V.

Compatible Drivers

Non Dimming Class II

Plug-in Drivers

**LED-DVR-24V-24W**

LED plug-in driver with DC 2.1 jack, 24V, 24W.

**LED-DVR-24V-36W**

LED plug-in driver with DC 2.1 jack, 24V, 36W.

**LED-DVR-24V-60W**

LED plug-in driver with DC 2.1 jack, 24V, 60W.

Hardwire Drivers

**LED-HWB-24V-24W**

LED hardwire driver with DC 2.1 jack, 24V, 24W.

**LED-HWB-24V-36W**

LED hardwire driver with DC 2.1 jack, 24V, 36W.

**LED-HWB-24V-60W**

LED hardwire driver with DC 2.1 jack, 24V, 60W.

Accessories

**LED-DIM-24V**

LED touch dimmer, 24V, for use with non-dimming drivers.

**LED-SP-4**

Optional harness for up to 4 runs, 24V.

Dimming Class II

Electronic Hardwire Drivers – Powered by Lutron®

**LED-HWBDIM2-24-40**

40W LED dimmable hardwire driver with DC 2.1 jack. 2-wire, 24V, powered by Lutron® Hi-Lume® 1% 2-wire 120V LED driver.

**LED-HWBDIM3-24-40**

40W LED dimmable hardwire driver with DC 2.1 jack. 3-wire, 24V, powered by Lutron® Hi-Lume® 1% Ecosystem/3-wire LED driver.

Accessories

**LED-SP-4**

Optional harness for up to 4 runs, 24V.