

# Britelux™



MOL.: 3 29/32 in. (99 mm)  
LCL.: 2 1/8 in. (64 mm)

**B10**



MOL.: 3 in. (76 mm)  
LCL.: 1 7/8 in. (48 mm)

**G16.5**



MOL.: 4 1/2 in. (114 mm)  
LCL.: 3 1/32 in. (77 mm)

**G25**



MOL.: 3 29/32 in. (99 mm)  
LCL.: 2 15/16 in. (75 mm)

**R20**



MOL.: 2 5/16 in. (69 mm)  
LCL.: 1 5/8 in. (41 mm)

**S11**

| Order code   | Description                    | Watts (W) | Base | Volts (V) | Lumen output (lm) | Average life (hrs) | Filament type | Finish | Case qty (inner/master) |
|--------------|--------------------------------|-----------|------|-----------|-------------------|--------------------|---------------|--------|-------------------------|
| <b>B10</b>   |                                |           |      |           |                   |                    |               |        |                         |
| 50522        | 25B10/CL/2M/E12/120V/STD BLX   | 25        | E12  | 120       | 220               | 2000               | CC-2V         | Clear  | 6/120                   |
| 50525        | 25B10/CL/2M/120V/STD BLX       | 25        | E26  | 120       | 220               | 2000               | CC-2V         | Clear  | 6/120                   |
| 50523        | 40B10/CL/2M/E12/120V/STD BLX   | 40        | E12  | 120       | 370               | 2000               | CC-2V         | Clear  | 6/120                   |
| 50526        | 40B10/CL/2M/120V/STD BLX       | 40        | E26  | 120       | 370               | 2000               | CC-2V         | Clear  | 6/120                   |
| 50524        | 60B10/CL/2M/E12/120V/STD BLX   | 60        | E12  | 120       | 550               | 2000               | C-7A/3        | Clear  | 6/120                   |
| <b>G16.5</b> |                                |           |      |           |                   |                    |               |        |                         |
| 10270        | 25G16.5/WH/2M/E12/120V/STD BLX | 25        | E12  | 120       | 180               | 2000               | CC-2V         | White  | 25/500                  |
| 50688        | 60G16.5/CL/2M/E12/120V/STD BLX | 60        | E12  | 120       | 650               | 2000               | CC-2V         | Clear  | 6/120                   |
| <b>G25</b>   |                                |           |      |           |                   |                    |               |        |                         |
| 50170        | 40G25/WH/2M/120V/STD BLX       | 40        | E26  | 120       | 400               | 2000               | CC-6          | White  | 6/60                    |
| <b>R20</b>   |                                |           |      |           |                   |                    |               |        |                         |
| 51080        | 30R20/FL/2M/120V/STD BLX       | 30        | E26  | 120       | 170               | 2000               | CC-6          | Frost  | 6/60                    |
| 61706        | 45R20/FL/2M/120V/STD BLX       | 45        | E26  | 120       | 380               | 2000               | CC-6          | Frost  | 6/60                    |
| <b>S11</b>   |                                |           |      |           |                   |                    |               |        |                         |
| 52167        | 40S11/CL/1M/E17/120V/STD BLX   | 40        | E17  | 120       | 400               | 1000               | C-7A          | Clear  | 25/500                  |

# General Service

| Order code   | Description               | Watts<br>(W) | Base | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish/<br>Color | Case<br>qty<br>(inner/master) |
|--|---------------------------|--------------|------|--------------|----------------------------|--------------------------|------------------|------------------|-------------------------------|
| <b>A15</b>   |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 1/2 in. (89 mm) LCL : 2 3/8 in. (60 mm)      |                           |              |      |              |                            |                          |                  |                  |                               |
| 50125  | 15A15/CL/5M/130V/STD      | 15           | E26  | 130          | 85                         | 5 000                    | C-9              | Clear            | 6/60                          |
| 50166  | 15A15/F/5M/130V/STD       | 15           | E26  | 130          | 80                         | 5 000                    | C-9              | Frost            | 6/60                          |
| 50145  | 25A15/CL/5M/130V/STD      | 25           | E26  | 130          | 135                        | 5 000                    | C-9              | Clear            | 6/60                          |
| 50126  | 25A15/F/5M/130V/STD       | 25           | E26  | 130          | 135                        | 5 000                    | C-9              | Frost            | 6/60                          |
| <b>A19</b>   |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 4 1/4 in. (108 mm) LCL : 3 1/8 in. (79 mm)     |                           |              |      |              |                            |                          |                  |                  |                               |
| 50941  | 15A19/CL/6M/130V/STD      | 15           | E26  | 130          | 80                         | 6 000                    | C-9              | Clear            | 6/120                         |
| 50931  | 25A19/CL/1M/120V/STD/4P   | 25           | E26  | 120          | 150                        | 1 000                    | C-9              | Clear            | 6/120                         |
| 50942  | 25A19/CL/6M/130V/STD/4P   | 25           | E26  | 130          | 105                        | 6 000                    | C-9              | Clear            | 6/120                         |
| 50943  | 25A19/F/6M/130V/STD/4P    | 25           | E26  | 130          | 100                        | 6 000                    | C-9              | Frost            | 6/120                         |
| <b>B8</b>  |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 5/32 in. (80 mm) LCL : 1 7/8 in. (48 mm)     |                           |              |      |              |                            |                          |                  |                  |                               |
| 50638  | 15B8/F/2.5M/E12/130V/STD  | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Frost            | 6/120                         |
| 50639  | 25B8/F/2.5M/E12/130V/STD  | 25           | E12  | 130          | 115                        | 2 500                    | C-7A             | Frost            | 6/120                         |
| <b>B10</b>   |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)  |                           |              |      |              |                            |                          |                  |                  |                               |
| 50611  | 15B10/CL/3M/E12/130V/STD  | 15           | E12  | 130          | 75                         | 3 000                    | C-7A             | Clear            | 6/120                         |
| 50543  | 25B10/CL/3M/E12/130V/STD  | 25           | E12  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50612  | 25B10/F/3M/E12/130V/STD   | 25           | E12  | 130          | 165                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)      |                           |              |      |              |                            |                          |                  |                  |                               |
| 50621  | 25B10/CL/3M/130V/STD      | 25           | E26  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm) |                           |              |      |              |                            |                          |                  |                  |                               |
| 50548  | 25B10/CL/3M/E14/130V/STD  | 25           | E14  | 130          | 165                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50551  | 25B10/F/3M/E14/130V/STD   | 25           | E14  | 130          | 195                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| <b>B10 Suitable for base up</b>                      |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 3 1/2 in. (89 mm) LCL : 2 1/8 in. (54 mm)      |                           |              |      |              |                            |                          |                  |                  |                               |
| 50624  | 25B10/F/3M/130V/STD       | 25           | E26  | 130          | 165                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50622  | 40B10/CL/3M/130V/STD      | 40           | E26  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50625  | 40B10/F/3M/130V/STD       | 40           | E26  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| MOL : 3 29/32 in. (99 mm) LCL : 1 25/32 in. (45 mm)  |                           |              |      |              |                            |                          |                  |                  |                               |
| 50544  | 40B10/CL/3M/E12/130V/STD  | 40           | E12  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50613  | 40B10/F/3M/E12/130V/STD   | 40           | E12  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50545  | 60B10/CL/3M/E12/130V/STD  | 60           | E12  | 130          | 430                        | 3 000                    | C-7A/3           | Clear            | 6/120                         |
| 50614  | 60B10/F/3M/E12/130V/STD   | 60           | E12  | 130          | 430                        | 3 000                    | C-7A/3           | Frost            | 6/120                         |
| MOL : 3 31/32 in. (101 mm) LCL : 1 25/32 in. (45 mm) |                           |              |      |              |                            |                          |                  |                  |                               |
| 50549  | 40B10/CL/3M/E14/130V/STD  | 40           | E14  | 130          | 280                        | 3 000                    | CC-2V            | Clear            | 6/120                         |
| 50552  | 40B10/F/3M/E14/130V/STD   | 40           | E14  | 130          | 280                        | 3 000                    | CC-2V            | Frost            | 6/120                         |
| 50550  | 60B10/CL/3M/E14/130V/STD  | 60           | E14  | 130          | 430                        | 3 000                    | C-7A/3           | Clear            | 6/120                         |
| 50553  | 60B10/F/3M/E14/130V/STD   | 60           | E14  | 130          | 430                        | 3 000                    | C-7A/3           | Frost            | 6/120                         |
| <b>BR30</b>  |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 5 1/8 in. (130 mm) LCL : 3 11/32 in. (85 mm)   |                           |              |      |              |                            |                          |                  |                  |                               |
| 50219  | 50BR30/FL/5M/130V/STD     | 50           | E26  | 130          | 240                        | 5 000                    | C-9              | Frost            | 6/60                          |
| 50077  | 65BR30/FL/5M/ES/130V/STD  | 65           | E26  | 130          | 470                        | 5 000                    | CC-6             | Frost            | 6/60                          |
| 50079  | 65BR30/SP/5M/ES/130V/STD  | 65           | E26  | 130          | 470                        | 5 000                    | CC-6             | Clear            | 6/60                          |
| <b>BR40</b>  |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 6 9/16 in. (167 mm) LCL : 4 1/4 in. (108 mm)   |                           |              |      |              |                            |                          |                  |                  |                               |
| 50080 <sup>1</sup>                                   | 65BR40/FL/5M/ES/130V/STD  | 65           | E26  | 130          | 470                        | 5 000                    | CC-6             | Clear            | 1/12                          |
| <b>C7</b>  |                           |              |      |              |                            |                          |                  |                  |                               |
| MOL : 2 1/8 in. (54 mm) LCL : 1 1/2 in. (38 mm)      |                           |              |      |              |                            |                          |                  |                  |                               |
| 50967  | 4C7/CL/3M/E12/125V/STD    | 4            | E12  | 125          | 25                         | 3 000                    | C-7A             | Clear            | 1/500                         |
| 22008  | 7C7/CL/2M/E12/120V/2P/STD | 7            | E12  | 120          | 26                         | 2 000                    | C-7A             | Clear            | 30/120                        |

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations, note that it will remain available until stock is depleted.

| Order code  | Description                | Watts<br>(W) | Base | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish | Case<br>qty<br>(inner/master) |
|---|----------------------------|--------------|------|--------------|----------------------------|--------------------------|------------------|--------|-------------------------------|
| <b>CA4.5</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 3/4 in. (70 mm) LCL : 1 5/8 in. (41 mm)     |                            |              |      |              |                            |                          |                  |        |                               |
| 52153   | 10CA4.5/CL/2M/E12/130V/STD | 10           | E12  | 130          | 40                         | 2 000                    | C-7A             | Clear  | 6/120                         |
| <b>CA8</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 19/32 in. (91 mm) LCL : 1 25/32 in. (45 mm) |                            |              |      |              |                            |                          |                  |        |                               |
| 52157   | 10CA8/F/2.5M/E12/130V/STD  | 10           | E12  | 130          | 50                         | 2 500                    | C-7A             | Frost  | 25/500                        |
| 50641   | 15CA8/CL/2.5M/E12/130V/STD | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Clear  | 6/120                         |
| 10269   | 15CA8/F/2.5M/E12/130V/STD  | 15           | E12  | 130          | 70                         | 2 500                    | C-7A             | Frost  | 25/500                        |
| 50643   | 25CA8/F/2.5M/E12/130V/STD  | 25           | E12  | 130          | 115                        | 2 500                    | C-7A             | Frost  | 6/120                         |
| 50642   | 40CA8/CL/2.5M/E12/130V/STD | 40           | E12  | 130          | 215                        | 2 500                    | C-7A             | Clear  | 25/500                        |
| 50644   | 40CA8/F/2.5M/E12/130V/STD  | 40           | E12  | 130          | 215                        | 2 500                    | C-7A             | Frost  | 25/500                        |
| <b>CA10</b>   |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 29/32 in. (99 mm) LCL : 2 1/8 in. (54 mm)   |                            |              |      |              |                            |                          |                  |        |                               |
| 51051   | 25CA10/CL/3M/130V/STD      | 25           | E26  | 130          | 120                        | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50629   | 25CA10/F/3M/130V/STD       | 25           | E26  | 130          | 115                        | 3 000                    | C-7A             | Frost  | 6/120                         |
| MOL : 4 3/32 in. (104 mm) LCL : 1 7/8 in. (48 mm)   |                            |              |      |              |                            |                          |                  |        |                               |
| 50615   | 25CA10/CL/3M/E12/130V/STD  | 25           | E12  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50618   | 25CA10/F/3M/E12/130V/STD   | 25           | E12  | 130          | 115                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| 50616   | 40CA10/CL/3M/E12/130V/STD  | 40           | E12  | 130          | 235                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50619   | 40CA10/F/3M/E12/130V/STD   | 40           | E12  | 130          | 205                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| 50617   | 60CA10/CL/3M/E12/130V/STD  | 60           | E12  | 130          | 455                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50620   | 60CA10/F/3M/E12/130V/STD   | 60           | E12  | 130          | 450                        | 3 000                    | CC-2V            | Frost  | 6/120                         |
| <b>F15</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 4 1/2 in. (115 mm) LCL : 2 9/16 in. (65 mm)   |                            |              |      |              |                            |                          |                  |        |                               |
| 50751   | 25F15/CL/2M/130V/STD       | 25           | E26  | 130          | 160                        | 2 000                    | CC-6             | Clear  | 25/100                        |
| 50750   | 40F15/CL/2M/130V/STD       | 40           | E26  | 130          | 305                        | 2 000                    | CC-6             | Clear  | 25/100                        |
| <b>G9.5</b>   |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 1/16 in. (52 mm) LCL : 1 1/2 in. (38 mm)    |                            |              |      |              |                            |                          |                  |        |                               |
| 52165   | 7.5G9.5/CL/1M/E12/130V/STD | 7            | E12  | 130          | 40                         | 1 000                    | C-7A             | Clear  | 25/500                        |
| <b>G11</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 5/8 in. (41 mm)    |                            |              |      |              |                            |                          |                  |        |                               |
| 50759   | 7.5G11/CL/1M/E12/130V/STD  | 7.5          | E12  | 130          | 510                        | 1 000                    | C-5              | Clear  | 25/500                        |
| 50761   | 7.5G11/CL/1M/130V/STD      | 7.5          | E26  | 130          | 40                         | 1 000                    | C-5              | Clear  | 25/500                        |
| <b>G13</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 2 3/8 in. (60.5 mm) LCL : 1 11/16 in. (43 mm) |                            |              |      |              |                            |                          |                  |        |                               |
| 50681   | 10G13/CL/3M/E12/130V/STD   | 10           | E12  | 130          | 50                         | 3 000                    | C-7A             | Clear  | 25/500                        |
| 50682   | 25G13/CL/3M/E12/130V/STD   | 25           | E12  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50684   | 60G13/CL/3M/E12/130V/STD   | 60           | E12  | 130          | 490                        | 3 000                    | C-7A             | Clear  | 25/500                        |
| <b>G16.5</b>  |                            |              |      |              |                            |                          |                  |        |                               |
| MOL : 3 in. (76 mm) LCL : 1 7/8 in. (48 mm)         |                            |              |      |              |                            |                          |                  |        |                               |
| 10334   | 5G16.5/CL/3M/E12/130V/STD  | 5            | E12  | 130          | 20                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 10268   | 10G16.5/CL/3M/E12/130V/STD | 10           | E12  | 130          | 50                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50660   | 15G16.5/CL/3M/E12/130V/STD | 15           | E12  | 130          | 70                         | 3 000                    | C-7A             | Clear  | 6/120                         |
| 50662   | 15G16.5/WH/3M/E12/130V/STD | 15           | E12  | 130          | 60                         | 3 000                    | C-7A             | White  | 6/120                         |
| 50652   | 25G16.5/WH/3M/E12/130V/STD | 25           | E12  | 130          | 120                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50777   | 25G16.5/CL/3M/E14/130V/STD | 25           | E14  | 130          | 160                        | 3 000                    | CC-6             | Clear  | 6/120                         |
| 50649   | 25G16.5/CL/3M/130V/STD     | 25           | E26  | 130          | 135                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50653   | 25G16.5/WH/3M/130V/STD     | 25           | E26  | 130          | 120                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50654   | 40G16.5/WH/3M/E12/130V/STD | 40           | E12  | 130          | 230                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50651   | 40G16.5/CL/3M/130V/STD     | 40           | E26  | 130          | 250                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50655   | 40G16.5/WH/3M/130V/STD     | 40           | E26  | 130          | 230                        | 3 000                    | CC-2V            | White  | 6/120                         |
| 50656   | 60G16.5/CL/3M/E12/130V/STD | 60           | E12  | 130          | 440                        | 3 000                    | CC-2V            | Clear  | 6/120                         |
| 50658   | 60G16.5/WH/3M/E12/130V/STD | 60           | E12  | 130          | 400                        | 3 000                    | CC-2V            | White  | 6/120                         |

Incandescent Lamps

| Order code   | Description                | Watts<br>(W) | Base | Volts<br>(V) | Lumens at 120 V<br>(lm) | Average life<br>(hrs) | Filament type | Finish     | Case qty<br>(inner/master) |
|--|----------------------------|--------------|------|--------------|-------------------------|-----------------------|---------------|------------|----------------------------|
| <b>G16.5 (cont.)</b>                                 |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 2 7/8 in. (73 mm) LCL : 2 1/16 in. (52 mm)     |                            |              |      |              |                         |                       |               |            |                            |
| 50779  | 25G16.5/WH/3M/E14/130V/STD | 25           | E14  | 130          | 150                     | 3 000                 | CC-6          | White      | 25/500                     |
| 50778  | 40G16.5/CL/3M/E14/130V/STD | 40           | E14  | 130          | 315                     | 3 000                 | CC-6          | Clear      | 25/500                     |
| 50782  | 60G16.5/WH/3M/E14/130V/STD | 60           | E14  | 130          | 580                     | 3 000                 | CC-6          | White      | 25/500                     |
| <b>G25</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 2 1/2 in. (114 mm) LCL : 3 1/32 in. (77 mm)    |                            |              |      |              |                         |                       |               |            |                            |
| 50199  | 25G25/CL/3M/130V/STD       | 25           | E26  | 130          | 135                     | 3 000                 | C-9           | Clear      | 6/60                       |
| 50196  | 25G25/WH/3M/130V/STD       | 25           | E26  | 130          | 115                     | 3 000                 | C-9           | White      | 6/60                       |
| 50222  | 40G25/CL/3M/130V/STD       | 40           | E26  | 130          | 255                     | 3 000                 | C-9           | Clear      | 6/60                       |
| 50155  | 40G25/WH/3M/130V/STD       | 40           | E26  | 130          | 230                     | 3 000                 | C-9           | White      | 6/60                       |
| <b>G30</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 5 13/32 in. (137 mm) LCL : 3 9/32 in. (83 mm)  |                            |              |      |              |                         |                       |               |            |                            |
| 50203  | 25G30/CL/3M/130V/STD       | 25           | E26  | 130          | 115                     | 3 000                 | C-9           | Clear      | 6/60                       |
| 50204  | 40G30/CL/3M/130V/STD       | 40           | E26  | 130          | 230                     | 3 000                 | C-9           | Clear      | 6/60                       |
| 50202  | 40G30/WH/3M/130V/STD       | 40           | E26  | 130          | 215                     | 3 000                 | C-9           | White      | 6/60                       |
| <b>G40</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 6 15/16 in. (176 mm) LCL : 3 29/32 in. (99 mm) |                            |              |      |              |                         |                       |               |            |                            |
| 50205  | 25G40/CL/3M/130V/STD       | 25           | E26  | 130          | 100                     | 3 000                 | C-9           | Clear      | 6/12                       |
| 50209  | 25G40/WH/3M/130V/STD       | 25           | E26  | 130          | 100                     | 3 000                 | C-9           | White      | 6/12                       |
| 50206  | 40G40/CL/3M/130V/STD       | 40           | E26  | 130          | 230                     | 3 000                 | C-9           | Clear      | 6/12                       |
| 50150  | 40G40/WH/3M/130V/STD       | 40           | E26  | 130          | 215                     | 3 000                 | C-9           | White      | 6/12                       |
| 50111  | 60G40/CL/3M/130V/STD       | 60           | E26  | 130          | 465                     | 3 000                 | C-9           | Clear      | 6/12                       |
| 50158  | 60G40/WH/3M/130V/STD       | 60           | E26  | 130          | 365                     | 3 000                 | C-9           | White      | 6/12                       |
| 50207  | 100G40/CL/3M/130V/STD      | 100          | E26  | 130          | 760                     | 3 000                 | C-9           | Clear      | 6/12                       |
| 50210  | 100G40/WH/3M/130V/STD      | 100          | E26  | 130          | 820                     | 3 000                 | C-9           | White      | 6/12                       |
| 50208  | 150G40/CL/3M/130V/STD      | 150          | E26  | 130          | 1 175                   | 3 000                 | C-9           | Clear      | 6/12                       |
| 50112  | 150G40/WH/3M/130V/STD      | 150          | E26  | 130          | 1 175                   | 3 000                 | C-9           | White      | 6/12                       |
| <b>PS25</b>  |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 6 15/16 in. (176 mm) LCL : 5 1/32 in. (128 mm) |                            |              |      |              |                         |                       |               |            |                            |
| 50071  | 300PS25/CL/5M/130V/STD     | 300          | E26  | 130          | 2 725                   | 5 000                 | C-9           | Clear      | 6/24                       |
| 50088  | 300PS25/F/5M/130V/STD      | 300          | E26  | 130          | 2 725                   | 5 000                 | C-9           | Frost      | 6/24                       |
| <b>PS30</b>  |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 8 1/16 in. (204 mm) LCL : 5 13/32 in. (137 mm) |                            |              |      |              |                         |                       |               |            |                            |
| 52428  | 300PS30/CL/120V/STD        | 300          | E26  | 120          | 3 600                   | 5 000                 | C-9           | Clear      | 6/24                       |
| <b>PS35</b>  |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 9 13/32 in. (239 mm) LCL : 6 1/2 in. (165 mm)  |                            |              |      |              |                         |                       |               |            |                            |
| 50225  | 300PS35/CL/5M/E39/130V/STD | 300          | E39  | 130          | 2 725                   | 5 000                 | C-9           | Clear      | 6/24                       |
| 50228  | 500PS35/F/5M/E39/130V/STD  | 500          | E39  | 130          | 6 055                   | 5 000                 | C-9           | Frost      | 6/24                       |
| <b>R14</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 2 1/8 in. (54 mm) LCL : 1 21/32 in. (42 mm)    |                            |              |      |              |                         |                       |               |            |                            |
| 50665  | 25R14/FL/1.5M/120V/STD     | 25           | E26  | 120          | 150                     | 1 500                 | CC-2V         | Clear      | 6/120                      |
| 50663  | 40R14/F/FL/1.5M/120V/STD   | 40           | E26  | 120          | 280                     | 1 500                 | CC-2V         | Frost      | 6/120                      |
| <b>R16</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 3 1/2 in. (89 mm)                              |                            |              |      |              |                         |                       |               |            |                            |
| 52168  | 25R16/SF/1.5M/E12/130V/STD | 25           | E12  | 130          | 120                     | 3 000                 | CC-2V         | Frost      | 25/500                     |
| <b>R19</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 3 31/32 in. (101 mm) LCL : 3 1/32 in. (77 mm)  |                            |              |      |              |                         |                       |               |            |                            |
| 50136  | 40R19/SW/1.5M/120V/STD     | 40           | E26  | 120          | 320                     | 1 500                 | CC-6          | Soft white | 6/60                       |
| 50138 <sup>1</sup>                                   | 75R19/SW/1.5M/120V/STD     | 75           | E26  | 120          | 770                     | 1 500                 | CC-6          | Soft white | 6/60                       |
| <b>R20</b>   |                            |              |      |              |                         |                       |               |            |                            |
| MOL : 3 29/32 in. (99 mm) LCL : 2 15/16 in. (75 mm)  |                            |              |      |              |                         |                       |               |            |                            |
| 50211  | 30R20/SP/5M/130V/STD       | 30           | E26  | 130          | 145                     | 5 000                 | C-9           | Clear      | 6/60                       |
| 61703  | 45R20/FL/5M/130V/STD       | 45           | E26  | 130          | 242                     | 5 000                 | CC-6          | Frost      | 6/60                       |
| 61705  | 45R20/SP/5M/130V/STD       | 45           | E26  | 130          | 242                     | 5 000                 | CC-6          | Frost      | 6/60                       |

<sup>1</sup> This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

| Order code   | Description                  | Watts<br>(W) | Base  | Volts<br>(V) | Lumens<br>at 120 V<br>(lm) | Average<br>life<br>(hrs) | Filament<br>type | Finish/<br>Color | Case<br>qty<br>(inner/master) |
|--|------------------------------|--------------|-------|--------------|----------------------------|--------------------------|------------------|------------------|-------------------------------|
| <b>S11</b>   |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 50789  | 5S11/CL/1M/E17/130V/STD      | 5            | E17   | 130          | 25                         | 1 000                    | C-7A             | Clear            | 25/500                        |
| 50143  | 10S11/CL/1M/E17/130V/STD     | 10           | E17   | 130          | 60                         | 1 000                    | C-7A             | Clear            | 6/120                         |
| 50165  | 10S11/F/1M/E17/130V/STD      | 10           | E17   | 130          | 60                         | 1 000                    | C-7A             | Frost            | 6/120                         |
| 50786  | 25S11/CL/1M/E17/130V/STD     | 25           | E17   | 130          | 130                        | 1 000                    | C-7A             | Clear            | 25/500                        |
| 50123  | 40S11/CL/1M/E17/130V/STD     | 40           | E17   | 130          | 275                        | 1 000                    | C-7A             | Clear            | 6/120                         |
| <b>S14</b>   |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 1/2 in. (38 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 59542  | 11S14/CL/8M/130V/STD         | 11           | E26   | 130          | 40                         | 8 000                    | C-9              | Clear            | 6/24                          |
| 50147  | 11S14/CL/3M/130V/STD         | 11           | E26   | 130          | 72                         | 3 000                    | C-9              | Clear            | 25/500                        |
| <b>T6</b>  |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 3 1/16 in. (78 mm) LCL : 1 9/16 in. (40 mm)    |                              |              |       |              |                            |                          |                  |                  |                               |
| 50667  | 15T6/CL/7.5M/E12/130V/STD    | 15           | E12   | 130          | 75                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| 50668  | 15T6/CL/7.5M/E12/145V/STD    | 15           | E12   | 145          | 90                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| 50675  | 15T6/CL/5M/E17/130V/STD      | 15           | E17   | 130          | 70                         | 5 000                    | C-5A             | Clear            | 12/120                        |
| 50676  | 15T6/CL/7.5M/E17/145V/STD    | 15           | E17   | 145          | 90                         | 7 500                    | C-5A             | Clear            | 12/120                        |
| <b>T6.5</b>  |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 13/32 in. (137 mm) LCL : 3 5/32 in. (80 mm)  |                              |              |       |              |                            |                          |                  |                  |                               |
| 51052  | 20T6.5/CL/5M/BA15d/130V/STD  | 20           | BA15d | 130          | 115                        | 5 000                    | C-8              | Clear            | 25/500                        |
| 50679  | 20T6.5/F/5M/BA15d/130V/STD   | 20           | BA15d | 130          | 115                        | 5 000                    | C-8              | Frost            | 12/120                        |
| 51056  | 25T6.5/CL/5M/BA15d/125V/STD  | 25           | BA15d | 125          | 180                        | 5 000                    | C-8              | Clear            | 25/500                        |
| 50729  | 25T6.5/F/7.5M/BA15d/145V/STD | 25           | BA15d | 145          | 145                        | 7 500                    | C-8              | Frost            | 25/500                        |
| 50672  | 25T6.5/CL/7.5M/E12/145V/STD  | 25           | E12   | 145          | 180                        | 7 500                    | C-8              | Clear            | 12/120                        |
| 50669  | 25T6.5/CL/5M/E17/130V/STD    | 25           | E17   | 130          | 135                        | 5 000                    | C-8              | Clear            | 12/120                        |
| 50670  | 25T6.5/CL/7.5M/E17/145V/STD  | 25           | E17   | 145          | 180                        | 7 500                    | C-8              | Clear            | 12/120                        |
| 50673  | 25T6.5/F/7.5M/E17/145V/STD   | 25           | E17   | 145          | 180                        | 7 500                    | C-8              | Frost            | 25/500                        |
| 50680  | 40T6.5/CL/5M/E17/130V/STD    | 40           | E17   | 130          | 280                        | 5 000                    | C-8              | Clear            | 12/120                        |
| 52191  | 40T6.5/F/5M/E17/130V/STD     | 40           | E17   | 130          | 210                        | 5 000                    | C-8              | Frost            | 25/500                        |
| <b>T7</b>  |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 5/16 in. (59 mm) LCL : 1 5/16 in. (33 mm)    |                              |              |       |              |                            |                          |                  |                  |                               |
| 52195  | 15T7/CL/1.5M/BA15d/120V/STD  | 15           | BA15d | 120          | 100                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 52196  | 15T7/F/1.5M/BA15d/130V/STD   | 15           | BA15d | 130          | 75                         | 1 500                    | C-7A             | Frost            | 25/1 000                      |
| 52192  | 15T7/CL/1.5M/E12/120V/STD    | 15           | E12   | 120          | 100                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 52201  | 25T7/CL/1.5M/E12/130V/STD    | 25           | E12   | 130          | 115                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| <b>T8</b>  |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 2 9/16 in. (65 mm) LCL : 1 5/8 in. (41 mm)     |                              |              |       |              |                            |                          |                  |                  |                               |
| 52198  | 25T8/CL/1.5M/BA15d/120V/STD  | 25           | BA15d | 120          | 220                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 52200  | 25T8/CL/1.5M/E12/120V/STD    | 25           | E12   | 120          | 220                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| 52197  | 25T8/CL/1.5M/E17/120V/STD    | 25           | E17   | 120          | 220                        | 1 500                    | C-7A             | Clear            | 25/1 000                      |
| <b>T10</b>   |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 in. (127 mm) LCL : 2 3/4 in. (70 mm)         |                              |              |       |              |                            |                          |                  |                  |                               |
| 50923  | 15T10/CL/3M/130V/STD         | 15           | E26   | 130          | 75                         | 3 000                    | C-5V             | Clear            | 6/120                         |
| 50925  | 25T10/CL/3M/130V/STD         | 25           | E26   | 130          | 135                        | 3 000                    | C-5V             | Clear            | 6/120                         |
| 50928  | 25T10/F/3M/130V/STD          | 25           | E26   | 130          | 135                        | 3 000                    | C-5V             | Frost            | 6/120                         |
| 50926  | 40T10/CL/3M/130V/STD         | 40           | E26   | 130          | 195                        | 3 000                    | C-5V             | Clear            | 6/120                         |
| 50929  | 40T10/F/3M/130V/STD          | 40           | E26   | 130          | 195                        | 3 000                    | C-5V             | Frost            | 6/120                         |
| <b>T10 HO</b>  |                              |              |       |              |                            |                          |                  |                  |                               |
| MOL : 5 13/32 in. (137 mm) LCL : 3 11/32 in. (85 mm) |                              |              |       |              |                            |                          |                  |                  |                               |
| 50149  | 25T10/CL/3M/HO/130V/STD      | 25           | E26   | 130          | 175                        | 3 000                    | C-8              | Clear            | 6/120                         |
| 50131  | 25T10/F/3M/HO/130V/STD       | 25           | E26   | 130          | 175                        | 3 000                    | C-8              | Frost            | 6/120                         |
| 50129  | 40T10/CL/3M/HO/130V/STD      | 40           | E26   | 130          | 300                        | 3 000                    | C-8              | Clear            | 6/120                         |
| 50132  | 40T10/F/3M/HO/130V/STD       | 40           | E26   | 130          | 300                        | 3 000                    | C-8              | Frost            | 6/120                         |