

ST <u>\</u> NP	RO					
Project:		Type:				
Drawn by:	y: Catalogue #:		Date:			
Individual Spe	ec Sheet					
24 V DC	<b>LED DRIVER</b>					
<b>HARDWIRE I</b> Class 2	DIMMABLE					
ORDERING INFO	RMATION					
Order code: Model number: UPC:	65741 LED/DRIVER/50W/24V/HW/D/STD 69549657410					
Case quantity:	20			• • • • • • • • • • • • • • • • • • • •	000 000 000 000 000 000 000 000 000 00	
PHYSICAL DATA Dimensions: Type: Color:	13 5/8" x 3 1/16" x 1 1/2" (346 mm x 78 Hardwire Driver - Dimmable White	mm x 37.5mm)			*** Ele 1	•
PERFORMANCE	DATA					
Output Power (W): Input Voltage (V AC): Output Voltage (V DC): Input Current (mA): Output Current (mA): Frequency (Hz): Power Factor: Environment: Operating Temperature: Dimmer Type:	50 100-130 24 410 2 083 50/60 ≥0.95 Dry -10°C to 40°C (14°F to 104°F) Forward and reverse					
COMPATIBLE DI	MMERS <sup>1</sup>					(x
LUTRON PD-6WCL,  1 This table shows dimmers that har being unique, various factors such variance in system performance. For additional support in operation. So	C03P  4, DSL06-1LZ, DSM10-1LZ, IPE04-1LZ  DVCL-153P, CTCL-153P, DVCL-253P, AYCL-253P, CTCL-153P, DVCL-253P, AYCL-253P, AY	n under normal conditions. Each installa on the circuit can, in certain instances, . Consult dimming system manufacturer able operation. Stanpro recommends to	cause for	warranty  IP 20 colored us Intertek	dimmable  constant volts  RUHS	dry location
•	,					

I accept the specifications of the luminaire configuration mentioned above. Name: Company: Signature: Date:

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

