

Project:		Type:
Drawn by:	Catalogue #:	Date:

Individual Spec Sheet

LED TAPE

LOW VOLTAGE TAPE

24 V

ORDERING INFORMATION

Order code:

Description: TAPE/16.4'/4.4W/40K/24V/IP22/180/8MM/STD

UPC: 069549658905

Case quantity:

PHYSICAL DATA

Reel Total Length: 16.4 ft. (5 m) Jacketed or Unjacketed: Unjacketed Wire gauge: 22 AWG

Number of LEDs: 180 LEDs per meter

55 LEDs per foot

Cuttable length: 1 $^{5}/_{16}$ in (33.3 mm) or every 6 LED chips

Maximum run length: 23 ft. (7 m)

Operating Temperature: -25°C / -13°F to 40°C / 104°F

PERFORMANCE DATA

Volts (V):

Color temperature (K): 4 000 (Cool white) Watts per length: 73 W per reel 14.5 W per meter

0.37 W per inch

Light output per length: 5 150 lm per reel

> 1 030 lm per meter 26 lm per inch

Efficacy (Im/W): 71 CRI: 90+ Life (hrs): 50 000 Beam angle (°): 120

¹ Typical Color temperature range: +/- 5 %
² Lumen values are derived from photometric testing. Initial lumens range: +/- 5 %
³ Life hours are derived from IESNA LM80-08 testing report and projected per IESNA TM-21-11 extrapolations

Extrusions, drivers and accessories are available (sold seperatly). Custom lenghts available upon request. Ask your sales representative for more information. This LED Tape is also available in 1.5 W and 2.9 W.

The state of the s





dimmable

dry location




This lighting equipment complies with Canadian standard ICES-005 for use in residential applications Data is based upon tests performed in a controlled environment.


Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.





DIMENSIONS





Qty	Description	Price	
I accept the specifications of the luminaire configuration mentioned above.			
name:			
Company:			
Name: Company: Signature:		Date:	

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

