

Project: _

Drawn by:

_____ Catalogue #: ____

Type: _

Date: _

Individual Spec Sheet

PFL LED BATTERY POWERED FLOOD LIGHT 3 Pre-Set Light Intensities

ORDERING INFORMATION

Order code: Model number: UPC: Case quantity: 67022 PFL/BTRY/100-240/50W/CW/YL/STD 069549670228 2

PHYSICAL DATA

Housing color: Housing material:

PERFORMANCE DATA

Watts (W):	50
Volts (V AC):	100-240
Color temperature (K)1:	Cool White
Lumen output (Im)2:	3 250
Efficacy (Im/W):	65
CRI:	70
Battery working time (h):	
20% Brightness:	12
50% Brightness:	6
100% Brightness:	3
Battery charging time (h):	6
Beam angle (°):	120
Amperage (A):	6.6
Battery specifications:	18.5 V 6.6 AH
Operating temp. range:	-10°C to 40°C (14°F to 104°F)
Dimming:	3 pre-set light Intensities

Yellow

Aluminum

 _1 Typical color temperature range: +/- 5 %. 2 Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %

ACCESSORIES (order separately)

Order code	Туре
67025	Tripod
67027	50 W replacement battery charger








67022

DIMENSIONS AND WEIGHT



Net weight (lbs) 9.26

Qty	Description	Price	
I accept the specific Name:	cations of the luminaire configuration mentioned above.		
Company: Signature:		Date:	
Data is based uno	n tests performed in a controlled environment. Actual perform	ance can vary depending on operating conditions. All products are	subject to

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice. Please contact your Stanpro customer service representative to confirm inventory levels at time of order.

