

# PASS & SEYMOUR®

Commercial Specification Grade Receptacles
Tamper-Resistant 15 & 20A, 125V


### TR5252, TR5352

# Safety- & code-driven solutions brought to you by Legrand<sup>®</sup>.

Corrosion-resistant plated-steel mounting strap, durable nylon faces, and triple-wipe power contacts combine with tamper-resistant shutters to deliver safe and reliable performance. Tamper-resistant feature helps you comply with 2014 NEC® Article 406.12 and get the job done right. Screw-pressure-plate back wiring ensures easy installation and excellent electrical connections. These UL listed receptacles are ideal for residential, multi-dwelling, commercial office, and hospitality applications.



#### FEATURES & BENEFITS



#### FIELD USES/VERTICAL MARKETS

- Residential
   Hospitality/Lodging
- Retail
- Multiple Dwelling
- Office



# PASS & SEYMOUR®

Commercial Specification Grade Receptacles Tamper-Resistant 15 & 20A, 125V

### ORDERING INFORMATION

Catalog Number	Rating A	v	Color	NEMA Configuration No.	
Duplex Receptacles Back & Side Wire					
TR5252I	15A	125V	Ivory	5-15R	
TR5252W	15A	125V	White	5-15R	
TR5252	15A	125V	Brown	5-15R	
TR5252GRY	15A	125V	Gray	5-15R	
TR5252BK	15A	125V	Black	5-15R	
TR5252RED	15A	125V	Red	5-15R	
TR5252LA	15A	125V	Light Almond	5-15R	
TR5352I	20A	125V	Ivory	5-20R	
TR5352W	20A	125V	White	5-20R	
TR5352	20A	125V	Brown	5-20R	
TR5352GRY	20A	125V	Gray	5-20R	
TR5352BK	20A	125V	Black	5-20R	
TR5352RED	20A	125V	Red	5-20R	
TR5352LA	20A	125V	Light Almond	5-20R	





NEMA 5-15R

NEMA

## PASS & SEYMOUR®




# Commercial Specification Grade Receptacles Tamper-Resistant 15 & 20A, 125V

### TECHNICAL INFORMATION

#### **3rd Party Compliance**

UL Listed, File Number E140596, Standard UL498 CSA/CUL approved, Standard CSA-C22.2 No. 42 Conforms to NEMA WD-1 and WD-6

#### **Performance Electrical** Dielectric Withstand Voltage Withstands 2000V minimum Maximum Working Voltage **Current Interrupting** Certified for current interrupting at full-rated current Temperature Rise Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current Mechanical Terminal Identification Terminal Identification in accordance with UL 498 (Brass, White, Green) **Terminal Accommodation** #14 AWG - #10 AWG copper conductor only. Product Identification Ratings are permanent part of the device Environmental Flammability Operating Temperature Maximum continuous +60°C, minimum -40°C without impact



Materials	
Face	Nylon
Back Body	Nylon
Line Contacts	.032 260 Brass
Mounting Strap	.042 Zinc-Plated Steel
Ground Contacts	.040 260 Brass
Pressure Plate	.080 Steel
Tamper-Resistant Shutters	Thermoplastic
Terminal Screws	#8 Tri-Drive Steel (Neutral = Nickel-Plated Steel)
Ground Screw	#8 Hex Tri-Drive Steel; Zinc Coating with Green Chromate
Auto-Ground Clip	Stainless Steel
Mounting Screws	Tri-Drive Steel

#### Warranty


1 Year

#### COMPLEMENTARY DEVICES & ACCESSORIES



# STRAIGHT BLADE RECEPTACLES

- Extra Heavy-Duty
- Heavy-Duty
- Hard Use
- Construction Grade
- Construction Grade Leaded
- Commercial Grade



#### PLUGTAIL™ DEVICES

- Extra Heavy-Duty SpecGrade
- Extra Heavy Duty Hospital Grade
- Extra Heavy-Duty Tamper-Resistant
- Extra Heavy-Duty Tamper-Resistant Hospital Grade



#### **DECORATOR DEVICES**

- Construction Grade Switches
- Specification Grade Combo Switches
- Construction Grade Receptacles
- Commercial Grade Receptacles
- Specification Grade Hallway Lights





#### **SWITCHES**

- Extra Heavy-Duty
- Extra Heavy-Duty Lighted
- Extra Heavy-Duty Security
- Extra Heavy-Duty Locking
- Hard Use
- Commercial Grade



#### GFCIs

- Specification Grade
- Hospital Grade
- PlugTail™



#### **WALL PLATES**

- TradeMaster® Thermoplastic Nylon
- Screwless Polycarbonate
- Stainless Steel
- Brass
- Aluminum
- Dustproof Stainless Steel Covers

#### ALSO AVAILABLE...

- Hospital Grade Devices
- PlugTail<sup>™</sup> Devices
- SPD & Isolated Ground Devices
- Ground Continuity Monitoring (GCM)
- Straight BladePlugs & Connectors
- Turnlok® Locking Devices
- Weatherproof Boxes & Covers
- IEC 309 Industrial Products
- Flexcor® Wire Mesh Grips



#### **Electrical Wiring Systems**

P.O. Box 4822 Syracuse, NY 13221-4822 Phone: 1.800.776.4035 www.legrand.us/passandseymour

570 Applewood Crescent Vaughan, Ontario L4K 4B4 Phone:905.738.9195 www.legrand.ca