



## ORA3-LED50

LED Wall/Flood Light



**WALL MOUNT WITH  
CONDUIT ENTRIES**



**KNUCKLE  
MOUNT**



**YOKE  
MOUNT**

Applications:  
Perimeter lighting in condos, townhouses, malls, commercial buildings.

### DESCRIPTION:

The ORA-LED series is a fully adjustable multi-purpose fixture that replaces traditional wall packs or floods. The ORA features a sleek elegant design with multiple mounting options.

### FEATURES:

- Fixture head may be aimed down or aimed out as needed.
- Three mounting options available - knuckle, yoke and wall mount.
- Wall light/flood light with wide beam optics.
- Wall mount version comes with back box that has 4 conduit entries on left and right sides, bottom and the back
- 347V unit comes with a thicker back box and is available in the wall mount version only.
- Architectural wall mount box (without conduit entries) available as an option sold separately.
- 0-10V dimming is standard.
- 0.15 meter power cord for knuckle and wall mount units and 0.5 meter power cord for yoke mount units.
- The ORA-LED Series can also be used as a sign light with different ARMS. Please view page 4 for dimensional drawings.

### SPECIFICATIONS

#### ORA3-LED50

Watts (W)	50.9
Lumens (Lm)	6455.9
Efficacy (Lm/W)	127
Replaces Up To	150W MH
Total Harmonic Distortion	15.3%
CRI	70
Power Factor	0.91
Voltage	120-277V*, 347V**
CCT	4000K*
Dimming	0-10V Dimming*
LED Life @ 100,000 Hours	77%
Finish	Bronze*, Custom Colour
Housing Details	Die Cast Aluminum
Lens Details	Clear PC Lens
Mounting	Knuckle, Yoke, Wall Mount
Operating Temp.	-40°C to +40°C
Certifications	UL, Wet Location, 5 Year Warranty
Factory Installed Options	Photocell, Dimming PIR Motion Sensor**
Options Sold Separately	Architectural Wall Mount Box (without conduit entries)

\* Standard Configuration

\*\* The WMCB back box must be ordered when ordering 347V, Photocell or Motion Sensor.

347V FIXTURES ARE DLC STANDARD



### SPECIFICATIONS

Model Number	Voltage (V)	Power (W)	Light Output (lm)	Efficacy (lm/W)	THD (%)	PF	CCT (K)	B-U-G
ORA3-LED50-B-4K-XXX-DIM-[KN;YK;WMC;WMCB]-[PC;Blank]	120-277	51	6456	127.0	15.3	0.915	4000	2-1-1
ORA3-LED50-C-4K-XXX-DIM-[WMCB]-[PC;Blank]	347	56	6471	115.5	14.5	0.954	4000	2-1-1

### AMPERAGE DRAW & SURGE PROTECTION

	CURRENT (A)					SURGE PROTECTION (kV)	
	120V	208V	240V	277V	347V	120-277V	347V
ORA3-LED50	0.44A	0.26A	0.22A	0.19A	0.16A	4kV	






### WEIGHT (lbs)

ORA3-LED50	6.1
------------	-----





### LUMEN MAINTENANCE

	50,000 HOURS	75,000 HOURS	100,000 HOURS
ORA3-LED50	87.8%	82.2%	76.9%

## DIMENSIONS:



## SIGN LIGHT DIMENSIONS:




## APPLICATION:




ORA3-LED50-B-4K-DIM  
MOUNTED AT 15 FEET 45 DEGREE TILT

Total Lumens = 6459    Mounting Height = 15 Ft    Maximum Calculated Value = 8.28 Fc



ORA3-LED50-B-4K-DIM  
MOUNTED AT 15 FEET

Total Lumens = 6459    Mounting Height = 15 Ft    Maximum Calculated Value = 10.67 Fc



## ORDERING GUIDE:

ORA3-LED	LED50		4K		DIM		
----------	-------	--	----	--	-----	--	--

Wattage	Voltage	Colour Temp.	Paint Finish	Dimming	Controls	Mounting
LED50 - 50W	B - 120-277V*	4K - 4000K*	BRZ - Bronze*	DIM-0-10V Dimming*	PC - Photocell**	KN - Knuckle
	C - 347V**		CC - Custom Colour		MS180DIM - Dimming PIR Motion Sensor**	YK - Yoke
						WMC - Wall Mount Box with Conduit Entries

\* Standard Configuration

\*\* Must order WMCB Back Box when ordering 347V, Photocell or Motion Sensor

347V FIXTURES WILL BE DLC STANDARD ONLY AND COMES WITH A DEEP BACKBOX ONLY

WMCB - Wall Mount Box with Conduit Entries for 347V Only

## ORDERING GUIDE - SIGN LIGHT:

ORA3-LED	LED50	B	4K		DIM		
----------	-------	---	----	--	-----	--	--

Wattage	Voltage	Colour Temp.	Paint Finish	Dimming	Mounting	Arm
LED50 - 50W	B - 120-277V*	4K - 4000K*	BRZ - Bronze*	DIM-0-10V Dimming*	KN - Knuckle	ARM1
			WHT - White			ARM2
			BLK - Black			ARM3
			CC - Custom Colour			ARM5

\* Standard Configuration

## FIELD INSTALLED ACCESSORIES

Ordering Guide For Accessories  
Check the items that you wish to order:

- ☐ 002255 - ORA 3/4 ARCHITECTURAL WALL MOUNT BRZ  
(This accessory is compatible only with ORA with Knuckle mount)