

RWF | PULSAIR™

WALL FAN HEATER



THE CLASSIC FAN HEATER

You won't find anything better than this efficient, durable and low noise fan heater. The Pulsair is extremely popular for many reasons. First, it can be recessed or surface mounted with a surface adapter (optional). It can also be mounted vertically or horizontally so that air can flow either up and down or right and left. Finally, the slim-line Pulsair can be recessed into a wall thickness of 2 in. to 3 in. While it's a winning heating solution for hallways or bathrooms, it can also be installed anywhere in the house, such as the office, or in commercial spaces. Its nichrome element provides instant heat. Available from 500 W to 2000 W, and from 120 V to 347 V, the Pulsair is recognized and recommended by those in the know.

VERY QUIET FAN HEATER

THE MOST RESISTANT GRILLE ON THE MARKET

INSTANT HEAT NICHROME ELEMENT

MULTIPLE INSTALLATION OPTIONS RECESSED, SURFACE MOUNTED, HORIZONTAL OR VERTICAL

ADAPTS TO MULTIPLE MARKETS AVAILABLE IN: 120 V, 208 V, 240 V AND 347 V

COLOURS

- **standard:** white, soft white
- **Orora (optional):** refer to www.stelpro.com/en-CA/Orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 20-gauge steel cabinet and 18-gauge steel grille
- quiet fan – 40 CFM (500 W to 1000 W models) – 75 CFM (1250 W to 2000 W models)
- thermal protection with automatic reset

ELEMENT

- nichrome element produces instant heat

CONTROL

- built-in thermostat (optional), 3 control knobs included (white, soft white and black)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended

INSTALLATION

- wall mounted
- recessed (wall must have a depth of 2 3/8 in. minimum)
- surface mounted with surface adapter (optional)
- four installation positions





WARRANTY

- five years

IDEAL FOR:

hallway, bathroom, locker room, office

FOUR INSTALLATION OPTIONS



°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_RWF_EN_190822

TECHNICAL SPECIFICATIONS

WITHOUT CONTROL		BUILT-IN THERMOSTAT		24 V CONTROL		POWER	VOLTAGE	FLOW	THROW DISTANCE		HEAT RISE		WEIGHT	
CODE	PRICE	CODE	PRICE	CODE	PRICE	WATTS	VOLTS	CFM	M	FT.	°C	°F	KG	LB
RWF0501	207.00	---	---	---	---	500	120	40	2	6'6"	22	39	2.7	6
RWF0508	205.00	---	---	---	---	500	208	40	2	6'6"	22	39	2.7	6
RWF0502	205.00	---	---	---	---	500/375	240/208	40	2	6'6"	22	39	2.7	6
RWF0503	260.00	RWF0503T	295.00	RWF0503C24	322.00	500	347	40	2	6'6"	22	39	2.7	6
RWF0751	219.00	---	---	---	---	750	120	40	2	6'6"	33	59	2.7	6
RWF0758	216.00	---	---	---	---	750	208	40	2	6'6"	33	59	2.7	6
RWF0752	216.00	---	---	---	---	750/563	240/208	40	2	6'6"	33	59	2.7	6
RWF0753	270.00	RWF0753T	305.00	RWF0753C24	332.00	750	347	40	2	6'6"	33	59	2.7	6
RWF1001	223.00	---	---	---	---	1000	120	40	2	6'6"	44	79	2.7	6
RWF1008	218.00	---	---	---	---	1000	208	40	2	6'6"	44	79	2.7	6
RWF1002	218.00	---	---	---	---	1000/750	240/208	40	2	6'6"	44	79	2.7	6
RWF1003	273.00	RWF1003T	308.00	RWF1003C24	335.00	1000	347	40	2	6'6"	44	79	2.7	6
RWF1251	235.00	---	---	---	---	1250	120	75	2.1	6'10"	29	53	2.7	6
RWF1258	230.00	---	---	---	---	1250	208	75	2.1	6'10"	29	53	2.7	6
RWF1252	230.00	---	---	---	---	1250/938	240/208	75	2.1	6'10"	29	53	2.7	6
RWF1253	285.00	RWF1253T	321.00	RWF1253C24	347.00	1250	347	75	2.1	6'10"	29	53	2.7	6
RWF1501	240.00	---	---	---	---	1500	120	75	2.1	6'10"	35	63	2.7	6
RWF1508	235.00	---	---	---	---	1500	208	75	2.1	6'10"	35	63	2.7	6
RWF1502	235.00	---	---	---	---	1500/1125	240/208	75	2.1	6'10"	35	63	2.7	6
RWF1503	289.00	RWF1503T	324.00	RWF1503C24	350.00	1500	347	75	2.1	6'10"	35	63	2.7	6
---	---	---	---	---	---	2000	120	75	2.1	6'10"	47	89	2.7	6
RWF2002	256.00	---	---	---	---	2000/1500	240/208	75	2.1	6'10"	47	89	2.7	6
RWF2008	256.00	---	---	---	---	2000	208	75	2.1	6'10"	47	89	2.7	6
RWF2003	311.00	RWF2003T	346.00	RWF2003C24	372.00	2000	347	75	2.1	6'10"	47	89	2.7	6

Add W for white or SW for soft white (consult the optional colours chart or contact your Stelpro representative for all other colours).
Models also available in 277 V. --- not available

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
RWFT1*	built-in single pole thermostat [120 V-347 V]	36.00
RWFT2	built-in double pole thermostat [120 V-347 V]	49.00
RWFS*	surface adapter	54.00

* Add W for white or SW for soft white.

TECHNICAL DRAWINGS

