# SMC402AD | MAESTRO™

### SMART CONTROLLER • THERMOSTAT

4000 W











## ORCHESTRATING COMFORT

Maestro is the first smart thermostat compatible with all your electric heating devices, such as baseboards, convectors and fan heaters. As the heart of your heating ecosystem, the Maestro controller•thermostat not only offers multiple features through its mobile app, it also gives you peace of mind, optimizes your comfort and saves energy. The Maestro solution is intuitive, accessible and smart. Maestro ensures you always stay comfortable by adjusting to your lifestyle. Turning your house into a smart home has never been easier!



#### SIMPLE AND INTUITIVE MOBILE APP

CONTROL AT YOUR FINGERTIPS WITH YOUR SMARTPHONE OR MOBILE DEVICE



### **CREATE PERSONALIZED ACTIVITIES**

THAT INTEGRATE EASILY INTO THE SMART HOME



#### **GEOFENCING FEATURE**

FOR OPTIMAL ENERGY EFFICIENCY



ACCESSORIES		
PRODUCT	DESCRIPTION	PRICE
SMAMPLIZB	Zigbee signal amplifier	100.00
SMREPETZB	Zigbee signal repeater	68.00

#### **COMPATIBILITY**

- Wi-Fi b/g/n
- Zigbee 3.0

#### **COLOUR**

black

#### **FINISH**

molded plastic

#### WATTAGE AND VOLTAGE

- 300 W to 4000 W @ 240 V
- 260 W to 3400 W @ 208 V
- 150 W to 2000 W @ 120 V

#### **CONTROL**

- access to the Maestro environment and application
- · colour touch screen
- graphical colour-code to ensure smart energy consumption
- optimized early start-up based on outdoor temperature

- radical temperature decrease detection (open-window feature)
- · weather conditions display
- energy consumption assessment
- home group monitoring and control

#### **ACCURACY**

- accurate ambient temperature control of ± 0.5 °C (1 °F)
- CSA C828-13
- temperature sensing with thermistor

#### TEMPERATURE RANGE

• 5 to 30 °C (from 41 to 86 °F)

#### WARRANTY

- · three years
- $\ensuremath{^*}$  study conducted by an independent university team

### TO DOWNLOAD THE APPLICATION:





#### TECHNICAL SPECIFICATIONS **PRODUCT** WATTS **VOLTAGE AMPERAGE FREQUENCY COLOUR PACKAGING UNIT PRICE** MINIMUM MAXIMUM AMPERES CODE **VOLTS** SMC402AD 150/260/300 2000/3400/4000 120/208/240 16.7 BLACK BOX 220.00

Dimensions: 5 3/8 in. (137 mm) wide, 5 3/8 in. (137 mm) high and 1 1/4 in. (32 mm) deep







