


LOGO! TD text display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8



Figure similar

| General information  |                                     |
|--|-------------------------------------|
| Product type designation   | Text display                        |
| Suitability for use  | Can be used with LOGO! 8 and higher |
| Display  |                                     |
| Design of display  | FSTN                                |
| Line display   |                                     |
| <ul style="list-style-type: none"> <li>Number of lines</li> <li>Number of characters per line</li> </ul>   | 6<br>20                             |
| Backlighting   |                                     |
| <ul style="list-style-type: none"> <li>Type of backlighting</li> </ul>   | LED                                 |
| Control elements   |                                     |
| Keyboard fonts   |                                     |
| <ul style="list-style-type: none"> <li>System keys                             <ul style="list-style-type: none"> <li>Number of configurable system keys</li> </ul> </li> <li>alphanumeric keyboard</li> </ul> | Yes<br>0<br>No                      |
| Installation type/mounting   |                                     |
| Wall mounting/direct mounting  | No                                  |
| Supply voltage   |                                     |
| Type of supply voltage   | AC/DC                               |
| Rated value (DC)   | 12 V; 12/24 V DC, 24 V AC           |
| Power loss   |                                     |
| Power loss, typ.   | 1.8 W; At 24 V DC                   |
| Interrupts/diagnostics/status information  |                                     |
| Diagnostics function   | No                                  |
| Degree and class of protection   |                                     |
| IP (at the front)  | IP65                                |
| Standards, approvals, certificates   |                                     |
| CE mark  | Yes                                 |
| UL approval  | Yes                                 |
| FM approval  | Yes                                 |
| KC approval  | Yes                                 |
| Marine approval  |                                     |
| <ul style="list-style-type: none"> <li>American Bureau of Shipping (ABS)</li> </ul>  | Yes                                 |
| Ambient conditions   |                                     |
| Ambient temperature during operation   |                                     |
| <ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>   | -20 °C; No condensation<br>55 °C    |

|  |   |
|--|---|
| <b>Ambient temperature during storage/transportation</b> |   |
| • min.   | -40 °C  |
| • max.   | 70 °C   |
| <b>Altitude during operation relating to sea level</b>   |   |
| • Ambient air temperature-barometric pressure-altitude   | Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)                              |
| <b>configuration / header</b>                            |   |
| <b>Configuration software</b>                            |   |
| • Configuration tool                                     | LOGO! Soft Comfort V8   |
| <b>Accessories</b>                                       |   |
| belongs to product                                       | LOGO!   |
| <b>Mechanics/material</b>                                |   |
| Design of housing  | plastic   |
| <b>Dimensions</b>  |   |
| Width  | 128.2 mm  |
| Height   | 86 mm   |
| Depth  | 38.7 mm   |
| Overall depth  | 38.7 mm   |
| <b>Weights</b>   |   |
| Weight, approx.  | 220 g   |
| <b>Scope of supply</b>                                   |   |
| Delivery quantity in pieces                              | 1   |
| <b>last modified:</b>                                    | 2/26/2021  |