SIEMENS

US2:52BP2W2 **Data sheet**



30mm BlackMax, Epoxy Coated Corrosion Resistant Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product **Enclosure** 1 number of command points delivery state as a kit No Actuator material of the actuating element plastic pull-to-unlatch mechanism type of unlocking device number of switching positions Front ring product component front ring Yes standard design of the front ring material of the front ring metal color of the front ring black Holder material of the holder Metal General technical data product component light source No degree of pollution protection class IP **IP66 Ambient conditions** ambient temperature during operation -35 ... +70 °C -40 ... +85 °C during storage

round

Actuator round

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Installation/ mounting/ dimensions shape of the installation opening

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2W2

Cax online generator

Certificates/ approvals **Further information**

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2W2

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2W2

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP2W2&lang=en

last modified: 5/31/2021 🖸