

Kellems® Wire Management Products

Features and Benefits

PolyTuff® I and PolyTuff® II Non-Metallic Liquidtight Conduit



All non-metallic construction ends fatigue and separation problems. They can be cut cleanly with a knife or PVC cutter so there are no jagged metal edges.





- PolyTuff® I Conduit, Gray**
- Rigid PVC core bonded to flexible PVC jacket
 - Approved for outdoor use and direct burial
 - UL Listed and CSA Certified



- PolyTuff® II Tubing, Black**
- PVC core with corrugated walls bonded to PVC jacket
 - Handles twists, turns, bends, switchbacks and straightaways with ease
 - UL Recognized and CSA Certified

PolyTuff® I Conduit		IP66 SUITABILITY	 
Trade Size (metric designator)	Feet (m)	Catalog Number	
¾ (12)	100 (30.5)	G1038	
	1200 (365.8)	G1038R1200	
½ (16)	100 (30.5)	G1050	
	1000 (304.8)	G1050R1000	
¾ (21)	100 (30.5)	G1075	
	500 (152.4)	G1075R500	
1 (27)	100 (30.5)	G1100	
	500 (152.4)	G1100R500	
1¼ (35)	100 (30.5)	G1125	
1½ (41)	50 (15.2)	G1150	
2 (53)	50 (15.2)	G1200	

Note: See pages X-58 and X-59, X-90 and X-91 for approved fittings.
See pages X-92 and X-93 for technical information and dimensional drawings.

PolyTuff® II Tubing		IP66 SUITABILITY	 
Trade Size (metric designator)	Feet (m)	Catalog Number	
¼ (10)	100 (30.5)	B2025	
	100 (30.5)	B2038	
¾ (12)	100 (30.5)	B2038	
	1200 (365.8)	B2038R1200	
½ (16)	100 (30.5)	B2050	
	1000 (304.8)	B2050R1000	
¾ (21)	100 (30.5)	B2075	
	800 (243.8)	B2075R800	
1 (27)	100 (30.5)	B2100	
	500 (152.4)	B2100R500	
1¼ (35)	100 (30.5)	B2125	
1½ (41)	50 (15.2)	B2150	
2 (53)	50 (15.2)	B2200	

Note: See page X-90 for approved fittings.
See pages X-92 and X-93 for technical information and dimensional drawings.

