





## 30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC

4 Pole, 5 Wire, Grounding











30A 3ØY **NEMA L26-30R** 

## **Connector Bodies**

| Watertight Safety-Sh                       | roud <sup>®</sup>      | IP66 SUITABILITY  | UL Type 4x, 12 |
|--|------------------------|-------------------|----------------|
| Description                                | Cord Dia.              | Catalog Number    |                |
| Black Valox® housing, white Valox® clamps. | .350"-1.150"<br>(9-29) | HBL2813SW HBL2803 | HBL2823SW -    |

| Insulgrip®                            |                        |                | IP20 SUITABILITY |         |         |
|---------------------------------------|------------------------|----------------|------------------|---------|---------|
| Description                           | Cord Dia.              | Catalog Number |                  |         |         |
| Black and white nylon.                | .350"-1.150"<br>(9-29) | HBL2813        | -                | HBL2823 | HBL2833 |
| Corrosion resistant,<br>yellow nylon. | .350"-1.150"<br>(9-29) | HBL28CM13      | -                | -       | -       |
| Black and white for flat cable.       | .350"-1.150"<br>(9-29) | HBL2813FC      | -                | -       | -       |
| All black nylon.                      | .350"-1.150"<br>(9-29) | HBL2813BK      | -                | -       | -       |

Note: See page B-52 for accessories.



**HBL2813SW** 



HBL2813

## Receptacles

| Watertight Safety-Shroud®                   | IP66 SUITABILITY |    | UL Type 4x, 12 |           |
|---|------------------|----|----------------|-----------|
| Description                                 | Catalog Number   | er |                |           |
| Gray Valox® housing and flange, back wired. | HBL2810SW        | -  | HBL2820SW      | HBL2830SW |
| Note: See page B-54 for accessories.        |                  |    |                |           |

| Safety-Shroud <sup>®</sup> Twist-Lock <sup>®</sup>  |                | IP20 SUITABILITY |   |   |  |
|---|----------------|------------------|---|---|--|
| Description   | Catalog Number |                  |   |   |  |
| Gray Valox® angle housing, one gang, back wired.    | HBL2810AR      | -                | - | - |  |
| Gray Valox® surface mounting, one gang, back wired. | HBL2810SR      | -                | - | - |  |
| Gray Valox® semi-flush, two gang, back wired.       | HBL2810SR2     | -                | - | - |  |

| Single Flush Receptacles                                 | IP20 SUITABILITY |         |           |         |  |
|--|------------------|---------|-----------|---------|--|
| Description  | Catalog Numbe    | er      |           |         |  |
| Black nylon face, back and side wired.                   | HBL2810          | HBL2800 | HBL2820   | HBL2830 |  |
| Black and white nylon, spring termination                | HBL2810ST        | -       | HBL2820ST | _       |  |
| Isolated ground, orange nylon face, back and side wired. | IG2810           | -       | -         | -       |  |
| Ring terminal connection.                                | HBL2810RT        | -       | _         | _       |  |
|  |                  |         |           |         |  |

Note: See page B-52 for accessories.


## Insulgrip® Flanged Receptacles

| Description               | Catalog Number |   |         |         |  |  |
|---------------------------|----------------|---|---------|---------|--|--|
| Nylon casing, back wired. | HBL2816        | - | HBL2826 | HBL2836 |  |  |

Note: See page B-52 for accessories.



**HBL2810SW** 



**HBL2820ST** 



**HBL2810SR** 

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)