

# Ground Fault Products



## Commercial Grade, Portable GFCI Line Cords

### Circuit Guard® Portable GFCI Single Outlet, 15A 120V AC - 12/3 SJEOW

| Description                    | Automatic Set  | Manual Set     |
|--------------------------------|----------------|----------------|
| 2' (60.9 cm) GFCI line cord.   | <b>GFP2CA</b>  | <b>GFP2CM</b>  |
| 25' (762.0 cm) GFCI line cord. | <b>GFP25CA</b> | <b>GFP25CM</b> |



### Circuit Guard® Portable GFCI Triple Tap Outlet, 15A 120V AC - 12/3 SJEOW

| Description                    | Automatic Set   | Manual Set      |
|--------------------------------|-----------------|-----------------|
| 2' (60.9 cm) GFCI line cord.   | <b>GFP2TTA</b>  | <b>GFP2TTM</b>  |
| 25' (762.0 cm) GFCI line cord. | <b>GFP25TTA</b> | <b>GFP25TTM</b> |



### Circuit Guard® OEM Equipment Integrated Cord Sets, 15A 120V AC - 14/3 SJEOW

| Description                             | Automatic Set  | Manual Set     |
|---|----------------|----------------|
| 15' (457.2 cm) GFCI with flying leads.  | <b>GFP15LA</b> | <b>GFP15LM</b> |
| 35' (1066.8 cm) GFCI with flying leads. | <b>GFP35LA</b> | <b>GFP35LM</b> |



### 15A GFCI In Line GFCI, Single and Triple Tap, 15A 120V AC - 12/3 SJTW

| Description                    | Automatic Set         | Manual Set            |
|--------------------------------|-----------------------|-----------------------|
| 2' (60.9 cm), 5-15 single tap. | <b>GFPIL15125A</b>    | <b>GFPIL15125M</b>    |
| 2' (60.9 cm), 5-15 triple tap. | <b>GFPIL15125TRIA</b> | <b>GFPIL15125TRIM</b> |



### 20A GFCI In Line GFCI, Locking, 20A 120V AC - 12/3 SJTW

| Description                  | Automatic Set        | Manual Set           |
|------------------------------|----------------------|----------------------|
| 2' (60.9 cm), L5-20 locking. | <b>GFPIL20125LKA</b> | <b>GFPIL20125LKM</b> |

### 20A GFCI In Line GFCI, Locking, 20A 250V AC - 12/3 SJTW

| Description                  | Automatic Set        | Manual Set           |
|------------------------------|----------------------|----------------------|
| 2' (60.9 cm), L6-20 locking. | <b>GFPIL20250LKA</b> | <b>GFPIL20250LKM</b> |



## Specifications

### Portable GFCI Line Cords

|                                  |  |
|----------------------------------|--|
| Trip Level                       | 4 to 6 mA.   |
| Trip Time                        | .025 sec. nominal.   |
| Frequency                        | 60 Hz.   |
| Voltage                          | 120/250V AC +10% - 15%. Incorporates no voltage release feature.   |
| Amperage                         | 15A/20A.   |
| Maximum Interrupting Capacity    | 2000A.   |
| Operating Temperature            | -35°C to 66°C or -30°F to 150°F.   |
| Maximum Humidity                 | 95%.   |
| Housing                          | High-impact, UV stabilized PVC. UL 94V-0 flammability classification. Meets UL and CSA watertight requirements. Adhesive bonded. |
| Visual Fault Indication Light On | Indicates fault.   |
| Listing and Standards            | Meets UL943 Class A, UL File E41978, CSA Certified.  |
| Codes                            | Meets all NEC® and CEC requirements.   |



NEC® is a registered trademark of the National Fire Protection Association (NFPA).