

## Slack Pulling Grips

Slack Pulling Grips are offered in three styles made of galvanized steel. The closed type is used when the cable end is accessible. When not accessible, there are split lace and split rod closing styles. All grips feature a single offset eye for easy attachment to a pulling line.


### IMPORTANT:

Read all breaking strength, safety and technical data relating to this product.

Refer to pages X-17 and X-18.

### Benefits

- Easy attachment to pulling lines
- Reusable rawhide lace for lace closure
- Galvanized steel for strength




### Slack Grip-Split Mesh, Rawhide Lace Closing, Offset Eye, Double Weave, Galvanized Steel

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs.	Working Load Lbs.	E Inches (cm)	M Inches (cm)	Catalog Number
<b>Standard</b>					
.75"-1.99" (1.90-2.51)	2,500	500	7" (17.78)	12" (30.48)	<b>03309003</b>
1.00"-1.24" (2.54-3.15)	3,500	700	8" (20.32)	15" (38.10)	<b>03309004</b>
1.25"-1.49" (3.17-3.78)	4,000	800	8" (20.32)	16" (40.64)	<b>03309005</b>
1.50"-1.74" (3.81-4.42)	4,000	800	9" (22.86)	17" (43.18)	<b>03309006</b>
1.75"-1.99" (4.44-5.05)	4,000	800	10" (25.40)	18" (45.72)	<b>03309007</b>
2.00"-2.49" (5.08-6.32)	4,000	800	10" (25.40)	19" (48.26)	<b>03309008</b>
2.50"-2.99" (6.35-7.59)	4,000	800	10" (25.40)	20" (50.80)	<b>03309009</b>
<b>Long</b>					
1.50"-1.99" (3.81-5.05)	4,000	800	9" (22.86)	25" (63.50)	<b>03309015</b>
2.00"-2.49" (5.08-6.32)	4,000	800	10" (25.40)	26" (66.04)	<b>03309016</b>
2.50"-2.99" (6.35-7.59)	4,000	800	10" (25.40)	29" (73.66)	<b>03309017</b>
3.00"-3.49" (7.62-8.86)	4,000	800	12" (30.48)	32" (81.28)	<b>03309018</b>
3.50"-3.99" (8.89-10.13)	4,000	800	12" (30.48)	35" (88.90)	<b>03309019</b>

### Benefits

- Easy attachment to pulling lines
- Galvanized steel for strength



### Slack Grip-Split Mesh, Rod Closing, Offset Eye, Single Weave, Galvanized Steel

Cable Diameter Range Inches (cm)	Approx. Breaking Strength Lbs.	Working Load Lbs.	E Inches (cm)	M Inches (cm)	Catalog Number
.50"-1.61" (1.27-1.55)	1,500	300	7" (17.78)	6" (15.24)	<b>03310001</b>
.62"-1.74" (1.57-1.88)	1,800	360	7" (17.78)	8" (20.32)	<b>03310002</b>
.75"-1.99" (1.90-2.51)	2,200	440	7" (17.78)	10" (25.40)	<b>03310003</b>
1.00"-1.24" (2.54-3.15)	3,400	680	8" (20.32)	12" (30.48)	<b>03310004</b>
1.25"-1.49" (3.17-3.78)	4,500	900	8" (20.32)	14" (35.56)	<b>03310005</b>
1.50"-1.74" (3.81-4.42)	5,800	1,160	9" (22.86)	15" (38.10)	<b>03310006</b>
1.75"-1.99" (4.44-5.05)	7,600	1,520	10" (25.40)	16" (40.64)	<b>03310007</b>
2.00"-2.49" (5.08-6.32)	9,000	1,800	10" (25.40)	19" (48.26)	<b>03310008</b>
2.50"-2.99" (6.35-7.59)	11,000	2,200	10" (25.40)	20" (50.80)	<b>03310009</b>
3.00"-3.49" (7.62-8.86)	12,000	2,400	12" (30.48)	21" (53.34)	<b>03310010</b>
3.50"-3.99" (8.89-10.13)	12,000	2,400	12" (30.48)	24" (60.96)	<b>03310011</b>

Note: E- Eye length. M-Mesh length at nominal diameter.

1. Replacement rawhide lace. Catalog number 20920002.
  2. See page X-35 for lace and rod closing instructions.
- See page X-18 for multiple cables in a single pulling grip.

Dimensions in Inches (mm)