

## inREACH™ Industrial and Industrial Weatherproof Cord Reels

Hubbell's newly redesigned inREACH™ Industrial and Industrial Weatherproof Cord Reels improve existing user safety and maximize efficiency by managing cord and power in a safe and organized manner, while also meeting the most demanding industrial environments needs for years with little to no maintenance.

inREACH™ Industrial and Industrial Weatherproof Cord Reels are listed to UL 355 and CSA, C22.2 No. 308 with a durable, lightweight low profile cast aluminum construction. inREACH™ Reels also feature a newly designed mounting plate that allows for a quick easy installation on any surface.

**inREACH™** *No matter what your need, Hubbell will always be inREACH™!*

## inREACH™ Industrial and Industrial Weatherproof Cord Reels

- » Durable, corrosion resistant cast aluminum construction
- » Yellow or white powder coat finish
- » Multi-position guide arm can be mounted in two positions
- » Positive latch mechanism automatically maintains desired cord length
- » Ratchet lock can be disengaged in field for constant tension applications
- » 16–10 AWG, 3 & 4 conductor cord for greater current carrying capacity
- » Available in 25ft, 35ft and 45ft lengths



### inREACH™ Industrial Cord Reels

Description	Amps	Volts AC	Cable Length		Weight Lbs. (kg)	Black Reel	White Reel	Yellow Reel
			Feet (m)	Cable Type				
Industrial Cord Reels	10	250	45 (13.7)	16/3 SJO	22.9 (10.4)	—	<b>HBLI45163</b>	<b>HBLI45163Y</b>
				16/4 SJO	23.6 (10.7)	—	<b>HBLI45164</b>	<b>HBLI45164Y</b>
			35 (10.7)	16/3 SJO	22.0 (10.0)	—	<b>HBLI35163</b>	<b>HBLI35163Y</b>
				16/4 SJO	22.7 (10.3)	—	<b>HBLI35164</b>	<b>HBLI35164Y</b>
			25 (7.6)	16/3 SJO	21.2 (9.6)	—	<b>HBLI25163</b>	<b>HBLI25163Y</b>
				16/4 SJO	21.8 (9.9)	—	<b>HBLI25164</b>	<b>HBLI25164Y</b>
	15	250	45 (13.7)	14/3 SJO	24.0 (10.9)	—	<b>HBLI45143</b>	<b>HBLI45143Y</b>
				14/4 SJO	25.4 (11.5)	—	<b>HBLI45144</b>	<b>HBLI45144Y</b>
			35 (10.7)	14/3 SJO	22.9 (10.4)	—	<b>HBLI35143</b>	<b>HBLI35143Y</b>
				14/4 SJO	24.0 (10.9)	—	<b>HBLI35144</b>	<b>HBLI35144Y</b>
			25 (7.6)	14/3 SJO	21.8 (9.9)	—	<b>HBLI25143</b>	<b>HBLI25143Y</b>
				14/4 SJO	22.7 (10.3)	—	<b>HBLI25144</b>	<b>HBLI25144Y</b>
20	250	45 (13.7)	12/3 SJO	26.5 (12.0)	<b>HBLI45123BLK</b>	<b>HBLI45123</b>	<b>HBLI45123Y</b>	
			12/3 SJO	26.5 (12.0)	—	<b>HBLIWC45123*</b>	—	
			12/4 SJO	29.8 (13.5)	—	<b>HBLI45124</b>	<b>HBLI45124Y</b>	
		35 (10.7)	12/3 SJO	24.9 (11.3)	—	<b>HBLI35123</b>	<b>HBLI35123Y</b>	
			12/4 SJO	26.5 (12.0)	—	<b>HBLI35124</b>	<b>HBLI35124Y</b>	
		25 (7.6)	12/3 SJO	23.4 (10.6)	—	<b>HBLI25123</b>	<b>HBLI25123Y</b>	
12/4 SJO	24.5 (11.1)	—	<b>HBLI25124</b>	<b>HBLI25124Y</b>				
30	250	45 (13.7)	10/3 SJO	32.4 (14.7)	—	<b>HBLI45103</b>	<b>HBLI45103Y</b>	
			40 (12.2)	10/4 SJO	33.7 (15.3)	—	<b>HBLI40104</b>	<b>HBLI40104Y</b>
		35 (10.7)	10/3 SJO	30.0 (13.6)	—	<b>HBLI35103</b>	<b>HBLI35103Y</b>	
			10/4 SJO	32.2 (14.6)	—	<b>HBLI35104</b>	<b>HBLI35104Y</b>	
		25 (7.6)	10/3 SJO	26.0 (11.8)	—	<b>HBLI25103</b>	<b>HBLI25103Y</b>	
10/4 SJO	29.1 (13.2)	—	<b>HBLI25104</b>	<b>HBLI25104Y</b>				



HBLI45163



HBLI45123BLK



HBLI45103Y

Dimensions in Inches (mm) Note: \*Supplied with White cable.