

# Straight Blade Devices

## 15 and 20 Ampere, 250 Volts

### HBL® Extra Heavy Duty Max Specification Grade Receptacles

Duplex	Color	Catalog Number	
Flush, nylon face, back and side wired, multiple drive screws.	Black	—	<b>HBL5462BK</b>
	Brown	<b>HBL5662</b>	<b>HBL5462</b>
	Gray	—	<b>HBL5462GY</b>
	Ivory	<b>HBL5662I</b>	<b>HBL5462I</b>
	Red	—	<b>HBL5462R</b>
Isolated ground <sup>A</sup> .	Orange	<b>IG5662</b>	<b>IG5462</b>

### Single

Flush, nylon face, back and side wired.	Brown	<b>HBL5661</b>	<b>HBL5461</b>
	Gray	—	<b>HBL5461GY</b>
	Ivory	<b>HBL5661I</b>	<b>HBL5461I</b>
	Red	—	<b>HBL5461R</b>
	White	—	<b>HBL5461W</b>
Isolated ground <sup>A</sup> .	Orange	<b>IG5661</b>	<b>IG5461</b>
Panel mount 1.94 in. (49.3) centers.	Brown	<b>HBL5684</b>	—
Ring terminal connection.	Brown	<b>HBL5661RT</b>	—

### Duplex and Single Panel Mount

Flush, nylon duplex face, side wired only.	Brown	<b>HBL5652</b>	—
	Ivory	<b>HBL5652I</b>	—
Panel mount 1.75 in. (44.5) centers.	Brown	<b>HBL5658</b>	—

Note: <sup>A</sup>See section N for additional information on isolated ground devices.

HP ratings are AC only.

See page A-47 for accessories.






See section O for wallplates.



**15A 250V**  
NEMA 6-15R  
UL CSA  
1.5 HP



**20A 250V**  
NEMA 6-20R  
UL CSA  
2 HP



Dimensions in Inches (mm)