Fire-Rated Poke-Throughs

Traditional Flush Duplex FRPT 3 Inch Core Hole Units, for Use In Concrete Floors

Flush Duplex FRPT, One-Piece Units

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
Flush Poke-Through	Black Brown Gray Ivory Gray Ivory	PT7FSDBLA PT7FSDBRA PT7FSDGYA PT7FSDIA PT7IGFSDGYA* PT7IGFSDIA*	Flush Brass Poke-Through	All Brass Black/Brass All Brass	PT7FSDBRS2A PT7FSDBRS3A PT7IGFSDBRSA*
 Complete assembled unit Pre-wired 20A duplex ra Non-metallic flip lid cover (2) ½ in. diameter low var feed-through holes Painted aluminum flanger 	eceptacle er with bltage		 Complete assembled unit includes: Pre-wired 20A duplex receptacle All brass or black non-metallic cover option Flip lid cover with (2) ½ in. diameter low voltage feed-through holes Solid brass flange 		

Note: *Includes pre-wired 20A isolated ground duplex receptacle.

Flush FRPT, Two-Piece Units

Description	Catalog Number
Multi-Channel Through-Floor Fitting with (1) ¾ in. EMT stem for power and	PT7FSD (with Junction Box) PT73SD (without Junction Box)
(2) ½ in. low voltage feed-through holes.	



Specifications:

• 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)

bShieldຶ

Complies with UL514A

- For 21/4 in. to 7 in. floor thickness
- UL installation spacing minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area

Service Fittings

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
Flush Aluminum Service Fitting	Black Brown Gray Ivory	FRFBLA FRFBRA FRFGYA FRFIA	Flush Brass Service Fitting	Solid Brass	FRFBRS2A
Complete assembled unit includes: • Pre-wired 20A duplex receptacle • Non-metallic flip lid cover with (2) ½ in. diameter low voltage feed-through holes • Painted aluminum flange			 Complete assembled unit includes: Pre-wired 20A duplex receptacle Solid brass flip lid cover with (2) ½ in. diameter low voltage feed-through holes Solid brass flange 		

Accessories

Description	Color	Catalog Number	Description	Color/Material	Catalog Number
Non-metallic Replacement Covers	Black Brown Gray Ivory	PFBRCBLA PFBRCBRA PFBRCGYA PFBRCIA	All Brass Replacement Covers	Solid Brass	BRS2RCA

Note: See page Q-35 for 3 Inch FRPT accessories. See page Q-43 for technical information.



