Non-Metallic Raceway



PW2 WallTrak[®] (Latching)

e Y	Description		Color	Length	Without Adhesive	With Adhesive
PW2 WallTrak®	Base and Cover Two channel raceway. Available in 5 ft. (1.5m) and 7 ft. (2.1m) lengths.		Office White	5 ft. 7 ft.	PW2BC5 PW2BC7 A: 1.04" (26.42) B: 2.12" (53.85)	PW2ABC5 PW2ABC7 A: 1.04" (26.42) B: 2.12" (53.85)
	Description Color 1-Gang Low Profile Box Office For shallow switches and receptacles. White See page T-63 for White plate options. Image: Color option	Catalog Number PDB12LP A: 4.90" (124.46) B: 3.25" (82.55) C: 1.25" (31.75)	Description Round Light To hang fixture	ing Fixture Bo	Color DX Office White Color White	Catalog Number PDB12LF A: 5.31" (134.87) B: 1.29" (32.77)
Boxes	1-Gang Standard Box For standard switches and receptacles. See page T-63 for recommended plate options. If using dual services, the PDB1DIV must be ordered.	PDB12S A: 4.90" (124.46) B: 3.25" (82.55) C: 1.78" (45.21)	For low voltage		nly. White	PDB12TGLV A: 4.90" (124.46) B: 5.06" (128.52) C: 2.44" (61.98)
Device Boxes	1-Gang Deep Box For deep devices or applications where additional room is beneficial. See page T-63 for recommended plate options. If using dual services, the PDB1DIV must be ordered.	PDB12D A: 4.90" (124.46) B: 3.25" (82.55) C: 2.44" (61.98)	additional roon	ces or application is beneficial. So "KP" plate optic e divider. ervices, ular run	ee page T-63	PDB12TGD A: 4.90" (124.46) B: 5.06" (128.52) C: 2.44" (61.98)
	1-Gang Divider For use with PDB12S and PDB12D 1-gang boxes. Required when two services are passing through box.	PDB1DIV A: 2.79" (70.86) B: 1.40" (35.56) C: 0.94" (23.88)		DB12TGD 2-gar n two services a nd mounting		PDB2DIV A: 4.62" (117.35) B: 2.76" (70.10) C: 0.94" (23.88)
	Internal Elbow Full capacity 11/4 in. bend radius internal elbow.	PW2IE* PW2IEBC** A: 2.83" (71.88) B: 2.32" (58.93) C: 2.83" (71.88)	External Elb Full capacity 1 bend radius external elbow	¼ in.	Office White	PW2EE* PW2EEBC** A: 5.00" (127.00) B: 2.32" (58.93) C: 5.00" (127.00)
	Flat Elbow Office Full capacity 1¼ in. bend radius flat elbow.	PW2FE* PW2FEBC** A: 3.94" (100.08) B: 3.94" (100.08) C: 1.11" (28.19)	Tee Full capacity 1 bend radius te		Office White	PW2TC* PW2TCBC** A: 5.42" (137.67) B: 3.91" (99.31) C: 1.90" (48.26)
Fittings	Splice Cover Office For covering potential openings White where two lengths of raceway come together.	PW2SC A: 1.11" (28.19) B: 2.30" (58.42) C: 1.11" (28.19)	Safety Strap For preventing with PW2 Wal Can also be us as a splice cov	potential tamp Trak Cover. sed	ering Office White	PW2SS A: 0.62" (15.75) B: 3.43" (87.12) C: 1.12" (28.45)
	Conduit Adapter/Ceiling Fitting For connecting conduit to raceway. Also use for ceiling feeds. Has combination ½ in., ¾ in. and 1 in. trade size KOs.	PW2CACF A: 4.18" (106.17) B: 3.32" (84.33) C: 4.20" (106.68)		PW2 WallTrak F 1 PremiseTrak F		PW2RED A: 1.62" (41.15) B: 2.40" (60.96) C: 1.15" (29.21)
	End Cap For closing end of PW2 WallTrak Raceway.	PW2EC A: 1.00" (25.40) B: 2.14" (54.36) C: 1.04" (26.42)				

Dimensions in Inches (mm)