

NOTES:

1. DIMENSIONS ARE INCHES ± .02

[mm] ± .5

- 2. CABLE SIZE: #6 AWG 2/0, COPPER ONLY
- 3. RATING 600V 300 AMPS
- 4. UL/c-UL ENCLOSURE TYPES 3R, 4X, 12, SEE INSTRUCTION SHEET
- 5. 1/2-20 UNF-2A X 1/2 LG. 7/32 SOCKET HEAD SET SCREWS, LEAD WIRE & COPPER SHEET NOT SNOWN.

HUBBELL CAT. NO.	COLOR
HBL300MBK	BLACK
HBL300MW	WHITE
HBL300MGN	GREEN
HBL300MR	RED
HBL300MBL	BLUE
HBL300MO	ORANGE
HBL300MBN	BROWN
HBL300MY	YELLOW
	•

		REVISED NOTE 3 F	EDOM .	RGP	11/01/17	REPAIRABLE
	5	600VAC/250VDC T PER DCN 23410 R	TO 600V	KGF	11/01/17	m
	4	08-15-14 UL FILE UPDATED MARKING UL1691-12 PER DCN 20659 CA	S PER	CAC	8/15/14	z
	3	3-21-12 DIM. 7.01 V (ADDED 6th RING TO PER DCN 18725 CZ	BODY)	CZH	3/21/12	ON-REF
	2	REMOVE MOLDED IN TO VIEWS, ADDING REFE SET TO THIS DRAWIN & FILE D-58726-01 ADD ± .02 & ± .5 TO CHANGED NOTE 4 LIST OF PARTS DESCRIPTION MALE PLUG BODY WAPLUG	RANCE NG NOTE 1 CRIPTION	TWB	12/15/04	NON-REPAIRABLE []
Ξ	1	PER DCN 11484 RELEASED PER DCN		TWB	6/26/03	ѿ
	SYM	MJM REVISIONS		APP	DATE	
7	THE DESIGN AND DIMENSIONS OF THE PRODUCT SHOWN ON THIS DRAWING ARE					

SUBJECT TO CHANGE WITHOUT NOTICE

SINGLE POLE 300A

MALE PLUGS

LIST OF PARTS

MATERIAL

TPE

NYLON

BRASS

BRASS NYLON

STEEL

COPPER

COPPER

FINISH SEE TABLE

BLACK

BLACK

NICKEL

Ē

TABLE

DESCRIPTION

MALE PLUG BODY

SLEEVE

SET SCREW

LEAD WIRE

COPPER SHEET

TOLERANCES UNLESS OTHERWISE SPECIFIED DECIMALS ANGLES

TITLE

WIRING DEVICE-KELLEMS HUBBELL INCORPORATED BRIDGEPORT, CT MJM APP. BY TWB ∞

DR. BY 1:1 CHK'D BY TWB DATE 6/11/03