





BENEFITS

- . Covers a wide range of applications with a lightweight, self-contained system and provides easy tool removal from continuous conductors with its C-shaped head.
- . Easy tool positioning with its 355° head ro
- . Patented rapid advance pump for faster crim
- . Exposed positive die lock buttons for easy die change out and die retention.
- . Handle trigger drain for convenient ram retraction.
- . Quality assuarance is provided with an audi "Pop-Off" pressure relief valve.
- . Comfort grip handles help ease operator fatigue with continuous use.
- . Long life expectancy from the company that provided the industry with the first self-contained hydraulic tool in 1934.
- . Rubber covered head and handles on Y750CHSXT for tool impact protection.
- . Supplied with high impact plastic carrying case.
- . Five year limited warranty and two years on all tools repaired by an Authorized BURNDY® Tool Repair Center.

TO ORDER BURNDY® PRODUC UNITED STATES: I-800-346-4175 (LONDONDE

CANADA: I-800-361-6975 (QUE I-800-387-6487 (ALL OTHER

FOR PRODUCT INFO: http://www.burndy.com DOCUMENTIYPE: Sales REL LEVEL: Released

TE	DESCRIPTION NGE RAM OPENING TO 1.653 MINIMUM			C′H′K.
00:00:00 AM			30317 TRF	MAC
	SPECIFICATIONS Y750HSXT			
	Force developed : I	2 tons	(
	Weight : I Length : 2	4.5 IDS. (6 3.96" (608	. 6 кд) mm)	
	Length : 2 Height : 2	.86" (73 mm	1)	
	Height : 2 Width : 8 Jaw opening : 1	.71° (222 m .653" (42 m	ım) ım) Minim	num
		VT		
	SPECIFICATIONS Y750CHS	A I		
	Force developed .	12 tons		
5	Weight :	17.2 lbs. ((7.8 kg)	
	Length : Height :	24.1" (612 3 06" (78 m	mm) ⁻	
otation.	Force developed : Weight : Length : Height : Width :	8.9" (226 n	nm)	
mps.	Jaw opening :	I./0" (43 n	nm)	
p.v.				
1	FOR USE ON			
	Turning Olym			
	Tension Sleeves Copper	# 8 sol50	0 k c m i l	ſ
lible	Aluminum	# 8sol587	-2kcmil	
11VIV		# 4-556.5kc	m I I	
	Taps Copper	# 4_so 5	Olkomil	
	Aluminum	# 14 \$013 # 8-500kcmi		
	Aerial Cable			
	Copper	# 6-500 k c m i	I	
	Terminals & Splices			
	Aluminum	# 8 -750kcm # 8-750kcmi	i I	ſ
	Copper ACSR	# 4-556 kcm	i I	
)	HYGROUND (Compressio	n Ground)		
	Copper	# 8-500 kcm	il.	
	Ground Rods	(cable/gro /2"-l" Di	und rod ameter)
		2.		
	ACCESSORIES			
	Cat. No. Descrij	ption	<u> </u>	
	PTI0024162 Plastic Y750HS	c Carrying (XT and Y750)	Case for CHSXT	
	V750UCVT V7500UC	YT SELE CONT		
CTS CALL	Y750HSXT, Y750CHS ITEM NO: 10074286,	10075515	IAINED I	00L
	CAT. NO: Y750HSXT,	Y750CHSXT /13/2007		
ERRY, NH)	CHECKER: M. CHIASSON 04	/13/2007 /13/2007		
BEC)	MFG APPVL: QA APPVL: J. BRODEUR 04	/19/2007		
PROVINCES) MKT APPVL: B. POIRIER 05 PROD FAM: TOOLS, HYDRAULI	/17/2007 C DRA	SCALE WING NO	: I : I Rev
w.burndy.c	OM DOCUMENT TYPE: Sales	<u>SIZE</u> 100	76340	D
	REL LEVEL: Released	U SHEE	TIOFI	-