60A, 125/250V, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY

Description	Cord Diameter	Catalog Number	
		60A 125/250V NEMA 14-60R UL CSA 3(2) HP	**60A 125/250V NEMA 14-60P** UL CSA 3(2) HP
Receptacle, black RTP.	–	**HBL9460A**	**–**
Plug, nylon.	.625"-1.310" (15.9-33.3)	**–**	**HBL9461C**
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	**–**	**HBL9462C**



HBL9460A

60A, 3Ø 250V AC, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY

Description	Cord Diameter	Catalog Number	
		60A 3Ø 250V AC NEMA 15-60R UL CSA 10 HP	**60A 3Ø 250V AC NEMA 15-60P** UL CSA 10 HP
Receptacle, black RTP.	–	**HBL8460A**	**–**
Plug, nylon.	.625"-1.310" (15.9-33.3)	**–**	**HBL8461C**
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	**–**	**HBL8462C**

HBL9461C



HBL9462C

60A, 3ØY 120/208V AC, 4 Pole, 4 Wire Non-Grounding, Receptacles and Plugs

IP20
SUITABILITY

Description	Cord Diameter	Catalog Number	
		60A 3ØY 120/208V AC NEMA 18-60R UL Listed 7.5 HP	**60A 3ØY 120/208V AC NEMA 18-60P** UL Listed 7.5 HP
Receptacle, black RTP.	–	**HBL7301A**	**–**
Plug, nylon.	.625"-1.310" (15.9-33.3)	**–**	**HBL7303C**
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	**–**	**HBL7302C**

Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See page A-50 for accessories.



HBL7301A

Dimensions in Inches (mm)