SIEMENS

Data sheet US2:52PP2W2



30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round **Enclosure** 1 number of command points delivery state as a kit No Actuator material of the actuating element plastic pull-to-unlatch mechanism type of unlocking device number of switching positions Front ring product component front ring Yes standard design of the front ring material of the front ring metal color of the front ring chrome Holder material of the holder Metal General technical data product component light source No degree of pollution protection class IP **IP66 Ambient conditions** ambient temperature during operation -35 ... +70 °C -40 ... +85 °C during storage Installation/ mounting/ dimensions shape of the installation opening round Certificates/ approvals

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2W2

Cax online generator

Further information

 $\underline{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52PP2W2}$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

 $\underline{https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2W2}$

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax de.aspx?mlfb=US2:52PP2W2&lang=en

last modified: 5/31/2021 🖸