
## SIEMENS

## Data sheet

## US2:52PP2A3A



30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1.73" (44 mm) Metal, Anodized Green 2 Position Maintained, Pull-to-Release with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Fig	ure	simi	lar

number of command points	1		
delivery state as a kit	No		
Actuator			
material of the actuating element	metal		
number of contact modules	1		
type of unlocking device	pull-to-unlatch mechanism		
number of switching positions	2		
Front ring			
product component front ring	Yes		
design of the front ring	standard		
material of the front ring	metal		
General technical data			
product function positive opening	Yes		
product component			
light source	No		
insulation voltage rated value	600 V		
surge voltage resistance rated value	4 kV		
protection class IP	IP66		
<ul> <li>of the terminal</li> </ul>	IP20		
thermal current	10 A		
Auxiliary circuit			
number of NC contacts for auxiliary contacts	1		
number of NO contacts for auxiliary contacts	1		
operational current at AC-15			
<ul> <li>at 110 V rated value</li> </ul>	60 A		
<ul> <li>at 230 V rated value</li> </ul>	30 A		
<ul> <li>at 400 V rated value</li> </ul>	15 A		
• at 500 V rated value	12 A		
Connections/ Terminals			
type of electrical connection	screw-type terminals		
tightening torque of the screws in the bracket	20 N·m		
tightening torque [lbf·in] with screw-type terminals	8 lbf·in		
Ambient conditions			
ambient temperature			
<ul> <li>during operation</li> </ul>	-35 +70 °C		
during storage	-40 +85 °C		
Installation/ mounting/ dimensions			
shape of the installation opening	round		

## Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10 Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2A3A

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2A3A

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2A3A

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52PP2A3A&lang=en

last modified:

12/21/2020 🖸