Eaton CHSPT2ULTRA

Catalog Number: CHSPT2ULTRA

Eaton SPD Type 2 CHSP Service Entrance Surge Protection, 120/240V line, 150V L-N, 300V L-L MCOV, 600V L-N, 1000V L-L, 800V N-G, 600V L-G VPR, 22 kA SCCR, NEMA 4, Single-phase, 60 Hz, 20 kA nominal current discharge, 108 kA surge current

General specifications

Product Name Catalog Number CHSPT2ULTRA Eaton CHSPT2 surge protection device UPC Product Length/Depth 786685436883 7 in **Product Height** Product Width 2.5 in

5 in

Warranty Limited lifetime

Product Weight

1 lb

Certifications

cUL Certified UL 1449 UL Recognized



Product specifications

Special features

Meets or exceeds the requirments specified in IBC ®2006, CBC2007, and UBC®Zone 4

Interrupt rating

200 kAIC

Phase

Single-phase

Enclosure

NEMA 4

Surge current

108 kA

Nominal Discharge Current 20 kA

Short-circuit rating 22000 kA

Type Surge protection device

Operating voltage 150V L-N, 300V L-L

Frequency rating 60 Hz

Operating temperature -40 to 50 °C

Voltage rating 120/240 V

Protection 600V L-N, 1000V L-L, 800V N-G, 600V L-G

Resources

Brochures

Product Family Guide Mike Holmes - Type 2 Surge Products Install sheets, CHSPT2 Storm season is coming. Are you prepared? Complete Home Protection, Publication No. FL010001EN / 3PC Complete Home Protection, Publication No. BR00414002E / VCG1502 Eaton Solutions, Publication No. SA00404006E / VCG1302 Ultra, Publication No. SA00414002E / VCG1503

Catalogs

Eaton's Volume 1—Residential and Light Commercial

Surge Protection

Installation instructions Complete Home Surge Protection

Specifications and datasheets Eaton Specification Sheet - CHSPT2ULTRA

Warranty guides Surge Protection Warranty WA00414003E



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia