

# Eaton LP-CC-25

Catalog Number: LP-CC-25

Eaton Bussmann series LP-CC fuse, Current-limiting time-delay fuse, Rejection style, 25 A, Dual, CC, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 20 kAIC at 300 Vdc|200 kAIC at 600 V, Melamine tube, 10, 600 V, 300 Vdc

## General specifications

Product Name	Catalog Number
Eaton Bussmann series LP-CC fuse	LP-CC-25
UPC	EAN
051712180283	5027590446983
Product Length/Depth	Product Height
.41 in	1.5 in
Product Width	Product Weight
.41 in	.15 lb
Warranty	Compliances
Not Applicable	CE Marked RoHS Compliant



## Product specifications

### Fuse indicator

Non-indicating

### Special features

Rejection style

### Interrupt rating

200 kAIC at 600 Vac

20 kAIC at 300 Vdc

### Number of elements

Dual

### Connection

Ferrule end x ferrule end

### Response time

12 sec at 200%

### Quantity

10

### Material

Melamine tube

### Amperage Rating

25 A

### Type

Current-limiting time-delay fuse

### Class

Class CC

### Voltage rating

600 Vac, 300 Vdc

### Application

Specialized circuits and industrial control

### Packaging type

Standard

## Resources

### Catalogs

[LP-CC-25~LOW PEAK CC TIME DELAY](#)

[Bussmann series complete full line catalog no. 1007](#)

[Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses](#)

### Multimedia

[Bussmann series Fuseology](#)

### Specifications and datasheets

[Eaton Specification Sheet - LP-CC-25](#)

### Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)