

Eaton C10G10

Catalog Number: C10G10

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 10 Amps, 120 kA Breaking capacity, class gG/gL, without indicator, compatible with a CHM Modular fuse holder

General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage cylindrical fuse	C10G10
	UPC
	051712754262
EAN	Product Length/Depth
5027590493390	38 mm
Product Height	Product Width
10 mm	10 mm
Product Weight	Warranty
8.2 g	1 year limited
Compliances	Certifications
CE Marked GoST-R RoHS Compliant	IEC 60269

Product specifications

Fuse indicator

Other

Construction size

10 x 38 mm

10 mm x 38 mm

Rated voltage AC

500 V

Connection

Ferrule end x ferrule end

Quantity

10

Suitable for

CHM Modular fuse holder

Material

Ceramic

Release characteristic

Other

Amperage Rating

10 A

Frequency rating - max

62 Hz

Utilization category

gL/gG (cable protection/equipment protection)

Watt losses

1 W

Fuse type

C10G

Type

fuse

Fuse shape

Cylindrical

Breaking capacity

120 kA

Fuse size

10 x 38 mm

Resources

Catalogs

Product overview for machinery

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA C08G, C08M, etc cylindrical fuselinks

CE C08G, C08M, etc cylindrical fuselinks

Specifications and datasheets

Eaton Specification Sheet - C10G10

Technical data sheets

720115 Cylindrical fuses

Frequency rating - min

45 Hz

Class

Class C gL/gG

Voltage rating

500 V

Application

for industrial applications

for general purpose use

Voltage type

AC



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)