

# Eaton XTCE040D00TD

Catalog Number: XTCE040D00TD

Eaton XT IEC contactor, 40A, 24-27 Vdc, ONO-0NC, 40A, Frame D, 55 mm, 3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton XT IEC contactor	XTCE040D00TD
<b>EAN</b>	<b>Product Length/Depth</b>
4015082777807	2.25 in
<b>Product Height</b>	<b>Product Width</b>
6 in	5 in
<b>Product Weight</b>	<b>Compliances</b>
2.4 lb	RoHS Compliant CE Marked
<b>Certifications</b>	<b>Catalog Notes</b>
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)

## Product specifications

### Frame size

55 mm

### Contact configuration

0 NO, 0 NC

### Coil voltage

24-27 Vdc

### Series

XT IEC

### Type

Full voltage non-reversing contactor

### HP rating - max

3, 5, 7.5/ 10, 15, 30, 40 hp (1/3PH  
@ 115,200,230/200,230,460,575 V)

### Continuous ampere rating

40 A

### Terminals

Screw terminals

### Operation

Non-reversing

### Amperage Rating

40A

### Number Of Poles

Three-pole

### Coil

24 Vdc

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Drawings

[XTCE\\_D AutoCAD 2D Footprint](#)

[XTCE\\_D 3D Model Xchange](#)

[XTCE\\_D 3D Inventor](#)

[XTCE\\_D 2D PDF](#)

[XTCE\\_D 2D Drawing Xchange](#)

### Specifications and datasheets

[Eaton Specification Sheet - XTCE040D00TD](#)

[Global Data Sheet - XTCE040D00TD](#)

### Warranty guides

[Selling Policy 25-000 - Distribution and Control Products and Services](#)