

Eaton XTCE250L22A

Catalog Number: XTCE250L22A

Eaton XT IEC contactor, 250A, 110 Vdc 40 Hz, 250 Vdc 60 Hz, 2NO-2NC, 250A, Frame L, 140 mm, 40-60 Hz, 75, 100, 200, 250 hp (3PH @200, 230, 460, 575 V), Three-pole, Screw terminals, Full voltage non-reversing contactor

General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE250L22A
EAN	Product Length/Depth
4015082082017	8.18897638 in
Product Height	Product Width
7.08661417 in	5.51181102 in
Product Weight	Compliances
.5070632 lb	CE Marked RoHS Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Frame size

140 mm

Contact configuration

2 NO, 2 NC

Coil voltage

110-250 Vdc

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

75, 100, 200, 250 hp (3PH @200,230,460,575 V)

Continuous ampere rating

250 A

Frequency rating

40-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

250 A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_L 2D PDF](#)

[XTCE_L AutoCAD 2D Footprint \(mm\)](#)

[XTCE_L AutoCAD 2D Footprint](#)

[XTCE_L 3D Model Xchange](#)

[XTCE_L 2D Drawing Xchange](#)

[XTCE_L 3D Inventor](#)

Specifications and datasheets

[Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)

[Eaton Specification Sheet - XTCE250L22A](#)

[Global Data Sheet - XTCE250L22A](#)