



Tape, Thread, Yellow Gas Line, PTFE, Listed

This product standard contains the required dimensional, mechanical, performance, and chemical characteristics of the products shown in this purchase order (as applicable to the product). Unless specified below, current revisions of national or international standards shall be applicable as of the date of Fastenal’s purchase order and must be adhered to in their entirety. If the order received does not meet these requirements, corrective action may be issued which could jeopardize your status as an approved supplier to Fastenal.



Part Number	Size	Thickness	Width	Length
		±0.0006	±0.02	±20
4203598	1/2"	0.00325	0.50	520

All dimensions are given in inches.

Specification Requirements:

- Dimensions: See Table Above
- Performance: Conforms to A-A-58092
- Material: 99.9% Virgin Polytetrafluoroethylene (PTFE)
- Appropriate Use Limitations: Service Temperature: -400°F to 560°F (-240°C to 293°C)
Pressure: 100 psig max.
Application: Naphtha, Benzene, Kerosene, Petroleum Oils, Natural Gas, Propane, Butane
- Density: 1.35 g/cm³ ± 5%
- Color: Yellow
- Marking: PROFITTER®
Part Number
Package markings shall comply with all marking requirements per UL 1321 as of the date of purchase A-A-58092
Appropriate Use Limitations (see above)
Country of Origin per 19 USC 1304
- Approvals and Listings: UL Approved – MH61975

RECORD OF REVISION CHANGES TO THIS DOCUMENT ARE LOCATED ON THE LAST PAGE

Page 2 of 2	Product Standard	REV-00
Date: February 24, 2021		TAPE.THRD.YGL.PTFE.L.PRO



Revision Level Changes to this Document

Document Name	Revision Level	Revision Date	Rationale for Revision
TAPE.THRD.YGL.PTFE.L.PRO	00	2/24/2021	Original document

The rationale above may not include all of the changes within each revision. A complete review of the Fastenal Product Standard is required.