



Halogen

Halogen lamps are designed to provide a crisp white light, a long life and constant lumen maintenance.

The use of halogen gas enables the filament to burn slower and to operate at a higher temperature, allowing for a whiter and brighter light output. Halogen also offers for a longer life and greater lumens per watt, making halogen lamps more efficient than regular incandescent lamps.

The crisp white light produced by halogen lamps reflects nicely on crystal by making it sparkle and enhances the beauty of crystal chandeliers.

Halogen lamps are dimmable and can be used in the most compact and stylish fixtures.

Many STANDARD halogen lamps are offered with a coating that filters UV rays and they can be identified by the UV STOP icon.

A19 Energy Saver



A19

Order code	Description	Watts (W)	Base	Volts (V)	Lumens output (lm)	Average life (hrs)	Finish	Operating position	Incan. equivalent (W)	Case qty (master)
A19										
62795 ^{1,2}	H43/A19/CL/120V/STD	43	E26	120	750	1 000	Clear	Universal	60	100
62796 ^{1,2}	H53/A19/CL/120V/STD	53	E26	120	1 050	1 000	Clear	Universal	75	100
62799 ^{1,2}	H43/A19/FR/120V/STD	43	E26	120	750	1 000	Frost	Universal	60	100
62801 ^{1,2}	H72/A19/FR/120V/STD	72	E26	120	1 490	1 000	Frost	Universal	100	100

JC & JD



JC (G4)



T3 (BA15d)



T3 (E11)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Case qty (inner/master)
JC (G4)								
51129	H10JC/CL/2M/G4/12V/STD	10	G4	12	130	2 000	Clear	100/1 000
51130	H20JC/CL/2M/G4/12V/STD	20	G4	12	300	2 000	Clear	100/1 000
67786	H20JC/CL/2M/G4/24V	20	G4	24	350	2 000	Clear	25/100
T3 (BA15d)								
69281	H75T3/CL/2M/BA15D/120V	75	BA15d	130	1 050	2 000	Clear	12/120
69245	H100T3/CL/2M/BA15D/130V/STD S2	100	BA15d	130	1 600	2 000	Clear	50/500
50885	H250T3/CL/2M/BA15D/130V/STD	250	BA15d	130	4 800	2 000	Clear	12/120
T3 (E11)								
69239	H50T3/CL/2M/E11/130V/STD S2	50	E11	130	1 120	2 000	Clear	50/500
69240	H75T3/CL/2M/E11/130V/STD S2	75	E11	130	1 350	2 000	Clear	50/500
69241	H100T3/CL/2M/E11/130V/STD S2	100	E11	130	1 800	2 000	Clear	50/500
69243	H250T3/CL/2M/E11/130V/STD S2	250	E11	130	4 800	2 000	Clear	50/500
69242	H150T3/CL/2M/E11/130V/STD S2	150	E11	130	2 000	2 000	Clear	50/500

¹This product is affected by provincial Energy Efficiency Regulations in Ontario, Quebec & British Columbia. Note that it will remain available until stock is depleted.

