

Eaton XTCE580N22A

Catalog Number: XTCE580N22A

Eaton XT IEC contactor, 630A, 110 Vac 40 Hz, 250 Vac 60 Hz, 2NO-2NC, 580A, Frame N, 250 mm, 40-60 Hz, 200, 200, 400, 600 hp (3PH @200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE580N22A
EAN	Product Length/Depth
4015082082161	9.13385827 in
Product Height	Product Width
11.65354331 in	1.77165354 in
Product Weight	Compliances
.5070632 lb	CE Marked RoHS Compliant
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Frame size

250 mm

Contact configuration

2 NO, 2 NC

Coil voltage

110-250 Vac, 40/60 Hz

Series

XT IEC

Type

Full voltage non-reversing contactor

HP rating - max

200, 200, 400, 600 hp (3PH @200,230,460,575 V)

Continuous ampere rating

580 A

Frequency rating

40-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

630A

Number Of Poles

Three-pole

Resources

Brochures

[XT IEC power control 580–2600A vacuum contactors](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_N AutoCAD 2D Footprint \(mm\)](#)

[XTCE_N 2D PDF](#)

[XTCE_N 3D Inventor](#)

[XTCE_N 2D Drawing Xchange](#)

[XTCE_N 3D Model Xchange](#)

[XTCE_N AutoCAD 2D Footprint](#)

Specifications and datasheets

[Global Data Sheet - XTCE580N22A](#)

[Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)

[Eaton Specification Sheet - XTCE580N22A](#)