

Eaton XTCE650N22A

Catalog Number: XTCE650N22A

Eaton XT IEC contactor, 700A, 110 Vac 40 Hz, 250 Vac 60 Hz, 2NO-2NC, 650A, Frame N, 250 mm, 40-60 Hz, 200, 250, 500, 600 hp (3PH @200, 230, 460, 575 V), Three-pole, 1041, , Screw terminals, FVNR

General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCE650N22A
EAN	Product Length/Depth
4015082082192	10.62992126 in
Product Height	Product Width
11.65354331 in	9.13385827 in
Product Weight	Compliances
.5070632 lb	RoHS Compliant CE Marked
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Contact configuration

2 NO, 2 NC

HP rating - max

200, 250, 500, 600 hp (3PH @200,230,460,575 V)

Operation

Non-reversing

Amperage Rating

700A

Number Of Poles

Three-pole

Frame size

250 mm

Coil voltage

110-250 Vac, 40/60 Hz

Series

XT IEC

Type

Full voltage non-reversing contactor

Continuous ampere rating

650 A

Frequency rating

40-60 Hz

Terminals

Screw terminals

Resistive load

1041

Resources

Brochures

[XT IEC power control 580–2600A vacuum contactors](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTCE_N AutoCAD 2D Footprint \(mm\)](#)

[XTCE_N 2D Drawing Xchange](#)

[XTCE_N 3D Inventor](#)

[XTCE_N AutoCAD 2D Footprint](#)

[XTCE_N 3D Model Xchange](#)

[XTCE_N 2D PDF](#)

Specifications and datasheets

[Global Data Sheet - XTCE650N22A](#)

[Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)

[Eaton Specification Sheet - XTCE650N22A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)